

# GAMMA LED BASIC 280 850LM 830 IP54 II KL. RCR OPAL (10W) 280MM

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	226724
<b>Ingress protection:</b>	IP54
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	10
<b>Luminous flux [lm]*:</b>	850
<b>Colour temperature [K]:</b>	3000
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	F
<b>Material of the body:</b>	PP
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

Surface-mounted, round LED light fitting, ingress protection class IP54, and an integrated energy-saving light source LED. White base; diffuser made of impact-resistant PC provides even light distribution and ensures a high impact resistance class (IK10). Additional overvoltage protection (SP1kV).

## APPLICATION

Surface mounted fitting intended for indoor use in representative rooms and passageways (large conference halls, hotel corridors, studies). Designed for mounting on ceilings and walls. Wide range of diameters and two diffuser versions allow for the same fitting to be used in rooms with different parameters. Well suited to be used as a basic or general interior light source.

The luminaire is intended for indoor traffic zones included in table 5.1 of the EN12464 standard.


# GAMMA LED BASIC 280 850LM 830 IP54 II KL. RCR OPAL (10W) 280MM

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	ø280/72
Nominal power [W]:	10	Mounting dimensions [mm]:	167
Rated power of the luminaire [W]:	10.40	Impact resistance:	IK10
Supply voltage [V]:	220-240	Ingress protection:	IP54
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous flux [lm]:	850	Working temperature [°C]:	from -10 to +25
Luminous efficacy [lm/W]:	80	Motion sensor:	yes
Energy efficiency class:	F	Dimensions of single box [mm]:	285/75/285
Electrical protection class:	II	Net weight [kg]:	0.430
Colour temperature [K]:	3000	Warranty [years]:	3
Colour rendering index:	>80	CE certificate:	<a href="#">391/2023</a>
SDCM:	≤ 3	Index:	226724
Max load (RCR) [W]:	200	EAN:	5905963226724
LED lifespan L70B50 [h]:	90000	Category type:	bulkheads
Surge protection [kV]:	1	Version:	280
Diffuser material:	PC	Vandalproof:	yes
Diffuser type:	OPAL	Light distribution type:	lambertian
Diffuser colour:	white	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Material of the body:	PP	Manual:	<a href="#">Download PDF</a>
Colour of the body:	white		

## LIGHT CURVES



# GAMMA LED BASIC 280 850LM 830 IP54 II KL. RCR OPAL (10W) 280MM


DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
754951	Gamma LED Basic 280 1000lm 840 (10W) - light module
754968	Gamma LED Basic 280 1500lm 840 (13W) - light module



Gamma LED Basic 280 1000lm 840  
(10W) - light module (754951)



Gamma LED Basic 280 1500lm 840  
(13W) - light module (754968)

Card creation date: 19 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 391/2023