

ANELLO LED 1178MM 9800LM 830 MAT WHITE (109W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	561757
Ingress protection:	IP20
Nominal power [W]:	109
Luminous flux [lm]*:	9800
Colour temperature [K]:	3000
Energy efficiency class:	A+
Material of the body:	aluminium

CHARACTERISTICS

Suspended LED luminaire in the shape of a circle, allowing for an interesting arrangement of large representative interiors. The luminaire is made of white powder-painted aluminum. Complete suspension system included (with central box) *.

Available in 2 versions:

- OPAL - spreads the light evenly,
- POINT - with an innovative lens system providing a low UGR (beam angle: 30 UGR <10; 60 UGR <19), thereby reducing glare.

Available on request:

- dimensions: 1700mm, 2200mm, 3000mm, 4100mm, 5100mm, 6000mm,
- luminaire luminous flux: from 7 560 lm to 49 390 lm,
- colors: RAL 9016, RAL 1013, RAL 1036, RAL 30001, RAL 8029, RAL 8028, RAL 7024, RAL 9005,
- color temperature: 4000K,
- DALI.

* for sizes 1135mm and 1500mm - 2 types of suspension system to choose (with central box or side box).

APPLICATION

ANELLO LED is an extremely impressive suspended luminaire, dedicated to such interiors as lobby, reception desks, shopping malls, and showrooms. It also works well in flats, perfectly matching the elegant surroundings.

ANELLO LED 1178MM 9800LM 830 MAT WHITE (109W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	109	Ingress protection:	IP20
Light source:	LED module	Mounting version:	suspended
Colour temperature [K]:	3000	Working temperature [°C]:	od 0 do +40
Luminous flux [lm]:	9800	Net weight [kg]:	10.400
Supply voltage [V]:	220-240	CE certificate:	34/2020
Diffuser type:	OPAL	Index:	561757
Frequency [Hz]:	50 - 60	EAN:	5905963561757
Beam angle [°]:	120	DC voltage range [V]:	50 - 60
Luminous efficacy [lm/W]:	90	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	white	Warranty [years]:	2
Energy efficiency class:	A+	Category of application:	architectural, HoReCa, commercial facilities, educational institutions
Electrical protection class:	I	Warranty [years]:	2
Dimensions (H/W/T/S) [mm]:	1178/85	Manual:	Download PDF
Material of the body:	aluminium		

Card creation date: 08 December 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 34/2020



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl