

TYTAN 2 LED BASIC 1150MM 4300LM 840 IP66 31W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	908736
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	31
Luminous flux [lm]*:	4300
Colour temperature [K]:	4000
Energy efficiency class:	C
Material of the body:	PC
Colour of the body:	RAL7035
Diffuser material:	PC

CHARACTERISTICS

TYTAN 2 LED BASIC is a basic line of lighting fixtures that provides an excellent alternative to traditional fluorescent lamps. The lighting fixture has been designed from scratch. TYTAN 2 LED BASIC includes new solutions which improve the light distribution and the temperature balance. The new LED panels ensure high luminous efficacy. This provides the required level of lighting along with significant energy savings. The lighting fixture includes many improvements which facilitate and speed up the installation process: a solution involving the integration of the diffuser with the LED panel, a diffuser suspension system, and adjustable mounting brackets with an installation tolerance of +/-50 mm. As a standard, the fixture is equipped with robust clips made of stainless steel (INOX). The body of the fixture and the diffuser are resistant to UV radiation.

APPLICATION

Die multifunktionale LED-Leuchte ist für den Einsatz in Bereichen mit hohen Anforderungen an Staub- und Wasserbeständigkeit konzipiert. Besonders empfehlenswert für die Beleuchtung öffentlicher Einrichtungen, einschließlich Krankenhausausbildungseinrichtungen, Hallen, Garagen, Durchgänge, Lagerhäuser, Geschäfte, Lebensmittelindustrie sowie Handels- und Serviceeinrichtungen für industrielle Lebensmittel (Fabriken, Labors), Lagerhäuser, Parkplätze (unterirdisch und mehrstöckig), Sportstadien, Transportterminals und unterirdische Gänge. Die Leuchte ist ideal für neue Beleuchtungsanwendungen und ersetzt herkömmliche Leuchtstofflampen durch energiesparende LED-Lösungen. Das Design ist für die Oberflächen- und Aufhängung geeignet.

TYTAN 2 LED BASIC 1150MM 4300LM 840 IP66 31W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	908736	Ingress protection:	IP66
EAN:	5905963908736	Mounting version:	surface, suspended
Light source:	LED module	Working temperature [°C]:	from -20 to +50
Rated power of the luminaire [W]:	31	Net weight [kg]:	1.300
Supply voltage [V]:	220-240	Category type:	battens
Frequency [Hz]:	50 - 60	AC voltage range [V]:	220 - 240
Luminous flux [lm]:	4300	LED lifespan L70B50 [h]:	104000
Luminous efficacy [lm/W]:	139	LED lifespan L80B10 [h]:	66000
Energy efficiency class:	C	LED lifespan L90B10 [h]:	32000
Electrical protection class:	I	Category of application:	industrial, commercial facilities
Colour temperature [K]:	4000	Mark D:	yes
Color rendering index (Ra) >:	80	Optics material:	PC
SDCM:	3	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Power factor:	0.90	Warranty [years]:	5
Exchangeable source:	yes	CE certificate:	274/2023
Surge protection [kV]:	1	ENEC Certificate:	0310/ENEC/23
Diffuser material:	PC	HACCP:	852/2004
Diffuser type:	mat	PZH certificate:	B-BK-60112-0280/2025
Material of the body:	PC	Environmental Product Declaration (EPD):	944/2026
Colour of the body:	RAL7035	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	1152/85/80	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Mounting dimensions [mm]:	800	Plik LDT:	Download
Impact resistance:	IK09		

TECHNICAL DETAILS



regulowane uchwyty / adjustable handles / einstellbare Halterungen



system zwieszania klosza / suspension system of the diffuser / hängende Diffusor




wybór miejsca zasilania / choosing a place of power supply / Stromversorgungsanschluss von mehreren Seite möglich

TYTAN 2 LED BASIC 1150MM 4300LM 840 IP66 31W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
907913	TYTAN LED. ATLAS LED - protective grid 1152mm
907920	TYTAN LED. ATLAS LED - protective grid 1432mm
16000507	Breathable gland gray M20*1.5 IP68
60000006	M16 stuffing box plug various PA black M-16 - BPM-21



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



TYTAN LED. ATLAS LED - protective grid 1152mm (907913)



TYTAN LED. ATLAS LED - protective grid 1432mm (907920)



Breathable gland gray M20*1.5 IP68 (16000507)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 04 May 2026
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 274/2023