

TYTAN 2 LED BASIC 1150MM 7150LM 840 IP66 AW3H 51W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|--------|
| Index: | 909603 |
| Ingress protection: | IP66 |
| Impact resistance: | IK09 |
| Rated power of the luminaire [W]*: | 51 |
| Luminous flux [lm]*: | 7150 |
| Colour temperature [K]: | 4000 |
| Energy efficiency class: | C |
| Material of the body: | PC |
| Colour of the body: | grey |
| Diffuser material: | PC |

CHARACTERISTICS

TYTAN 2 LED BASIC is a basic line of lighting fixtures that provides an excellent alternative to traditional fluorescent lamps. The lighting fixture has been designed from scratch. TYTAN 2 LED BASIC includes new solutions which improve the light distribution and the temperature balance. The new LED panels ensure high luminous efficacy. This provides the required level of lighting along with significant energy savings. The lighting fixture includes many improvements which facilitate and speed up the installation process: a solution involving the integration of the diffuser with the LED panel, a diffuser suspension system, and adjustable mounting brackets with an installation tolerance of +/-50 mm. As a standard, the fixture is equipped with robust clips made of stainless steel (INOX). The body of the fixture and the diffuser are resistant to UV radiation.

APPLICATION

Multifunkční LED svítidla je určena pro použití v oblastech s vysokými požadavky na odolnost vůči prachu a vodě. Zvláště se doporučuje pro osvětlení veřejných zařízení, včetně nemocnic, vzdělávacích zařízení, hal, garáží, pasáží, skladů, obchodů, potravinářského průmyslu, obchodních a průmyslových objektů (továrny, laboratoře), skladů, parkovišť (podzemních a víceúrovňových), sportovních stadionů, dopravní terminály a podzemní chodby. Svítidlo je ideální pro nové osvětlovací aplikace a zároveň nahrazuje tradiční zářivková svítidla energeticky úspornými LED řešeními. Jeho konstrukce je přizpůsobena pro povrchovou a závěsnou montáž.

TYTAN 2 LED BASIC 1150MM 7150LM 840 IP66 AW3H 51W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------|----------------------------------|---|
| Index: | 909603 | Impact resistance: | IK09 |
| EAN: | 5905963909603 | Ingress protection: | IP66 |
| Light source: | LED module | Mounting version: | surface, suspended |
| Rated power of the luminaire [W]: | 51 | Working temperature [°C]: | from 0 to +35 |
| Supply voltage [V]: | 220-240 | Emergency lighting [h]: | 3 |
| Frequency [Hz]: | 50 - 60 | Net weight [kg]: | 2 |
| Luminous flux [lm]: | 7150 | Category type: | battens |
| Luminous efficacy [lm/W]: | 140 | Autotest: | yes |
| Energy efficiency class: | C | AC voltage range [V]: | 220 - 240 |
| Electrical protection class: | I | LED lifespan L70B50 [h]: | 103000 |
| Colour temperature [K]: | 4000 | LED lifespan L80B20 [h]: | 65000 |
| Colour rendering index: | >80 | LED lifespan L90B10 [h]: | 32000 |
| SDCM: | ≤ 3 | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Power factor: | 0.97 | Category of application: | commercial facilities, industrial |
| Battery life [h:min]: | 3 | Mark D: | yes |
| Exchangeable source: | yes | Warranty [years]: | 2 / 0.5 (battery) |
| Diffuser material: | PC | CE certificate: | 274/2023 |
| Diffuser type: | MAT | ENEC Certificate: | 0310/ENEC/23 |
| Material of the body: | PC | PZH certificate: | B-BK-60212-0152/20 |
| Colour of the body: | grey | HACCP: | 852/2004 |
| Dimensions (H/W/T/S) [mm]: | 1152/85/80 | Manual: | Download PDF |
| Mounting dimensions [mm]: | 800 | | |

TECHNICAL DETAILS



regulowane uchwyty / adjustable handles / einstellbare Halterungen



system zwieszania klosza / suspension system of the diffuser / hängende Diffusor




wybór miejsca zasilania / choosing a place of power supply / Stromversorgungsanschluss von mehreren Seite möglich

TYTAN 2 LED BASIC 1150MM 7150LM 840 IP66 AW3H 51W

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|----------|---|
| 908200 | TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) |
| 907913 | TYTAN LED. ATLAS LED - protective grid 1152mm |
| 907920 | TYTAN LED. ATLAS LED - protective grid 1432mm |
| 16000507 | Breathable gland gray M20*1.5 IP68 |
| 60000006 | M16 stuffing box plug various PA black M-16 - BPM-21 |



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



TYTAN LED. ATLAS LED - protective grid 1152mm (907913)



TYTAN LED. ATLAS LED - protective grid 1432mm (907920)



Breathable gland gray M20*1.5 IP68 (16000507)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 24 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 274/2023