

DIONE LED PLUS 1450 LM 840 IP65 I KL. DALI RCR OPAL BIAŁY 13W CORRIDOR

DETAILED CARD



TECHNICAL PARAMETERS

Index:	950131.
Ingress protection:	IP65
Impact resistance:	IK10
Nominal power [W]:	13
Luminous flux [lm]*:	1450
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy-saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows keeping the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency, and optimal use of electricity (Power Factor).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS 1450 LM 840 IP65 I KL. DALI RCR OPAL BIAŁY 13W CORRIDOR

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	13	Ring colour:	white
Index:	950131.	Dimensions (H/W/T/S) [mm]:	ø340/115
Colour temperature [K]:	4000	Mounting dimensions [mm]:	140
EAN:	5905963950131	Impact resistance:	IK10
Luminous flux [lm]:	1450	Ingress protection:	IP65
Light source:	LED module	Mounting version:	surface
Diffuser type:	OPAL	Working temperature [°C]:	from -20 to +35
Rated power of the luminaire [W]:	16	Dimensions of single box [mm]:	340/340/115
Motion sensor:	yes	Net weight [kg]:	1.300
Supply voltage [V]:	220-240	Gross weight [kg]:	1.480
DIMM DALI:	yes	Warranty [years]:	5
Corridor function:	yes	CE certificate:	44/2022
Luminous efficacy [lm/W]:	89	Permeability factor of the diffuser:	0.73
Energy efficiency class:	E	Category type:	bulkheads
Electrical protection class:	I	Category of application:	HoReCa, commercial facilities, educational institutions
Colour rendering index:	>80	Luminaire rated power O_{min} [W]:	16.10
SDCM:	≤ 3	AC voltage range [V]:	220-240
Power factor:	0.94	DC voltage range [V]:	176-276
Max load (RCR) [W]:	400	LED lifespan L70B50 [h]:	>54000
Beam angle [°]:	120	LED lifespan L80B20 [h]:	>54000
Diffuser material:	PC	LED lifespan L90B10 [h]:	>33000
Diffuser colour:	white	Light distribution type:	open space
Material of the body:	ABS	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	white	Manual:	Download PDF
Ring material:	ABS	PZH certificate:	B-BK-60212-0619/20

DIONE LED PLUS 1450 LM 840 IP65 I KL. DALI RCR OPAL BIAŁY 13W CORRIDOR

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant (120DL118)

Card creation date: 04 October 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 44/2022