

# SITE LITE FUTURE LED 2200LM 840 24-48V IP44 III KL. 5M WT. CEE Z GNIAZDEM CEE SZARY (20W) Z MAGNESAMI

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	621291
<b>Ingress protection:</b>	IP44
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	20
<b>Colour temperature [K]:</b>	4000
<b>Luminous flux [lm]*:</b>	2200
<b>Electrical protection class:</b>	III
<b>Material of the body:</b>	PP
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	milky

## CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

## APPLICATION

The luminaire will provide precise illumination of the workplace.

# SITE LITE FUTURE LED 2200LM 840 24-48V IP44 III KL. 5M WT. CEE Z GNIAZDEM CEE SZARY (20W) Z MAGNESAMI

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	621291	<b>Colour of the body:</b>	graphite
<b>Category type:</b>	general construction site lighting	<b>Impact resistance:</b>	IK10
<b>Light source:</b>	LED module	<b>Ingress protection:</b>	IP44
<b>Nominal power [W]:</b>	20	<b>Plug type:</b>	CEE
<b>Luminous flux [lm]:</b>	2200	<b>Socket type:</b>	CEE
<b>Supply voltage [V]:</b>	24-48	<b>Sockets:</b>	1
<b>Electrical protection class:</b>	III	<b>Cable length [m]:</b>	5
<b>Colour temperature [K]:</b>	4000	<b>Magnet:</b>	yes
<b>Diffuser material:</b>	PC	<b>Net weight [kg]:</b>	1.400
<b>Diffuser type:</b>	milky	<b>Dimensions (H/W/T/S) [mm]:</b>	ø198/154
<b>Material of the body:</b>	PP	<b>Manual:</b>	<a href="#">Download PDF</a>

Card creation date: 01 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 272/2023