

# MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI SCHUKO WYŁĄCZNIK

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	247057
<b>Ingress protection:</b>	IP54
<b>Impact resistance:</b>	IK10
<b>Rated power of the luminaire [W]*:</b>	32
<b>Supply voltage [V]:</b>	220-240
<b>Luminous flux [lm]*:</b>	4300
<b>Energy efficiency class:</b>	D
<b>Electrical protection class:</b>	I
<b>Colour temperature [K]:</b>	4000

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle. A rubber cable H07RN-F 3x1.5 mm<sup>2</sup> (3 m) comes as standard.

## APPLICATION

The luminaire will provide precise illumination of the workplace.

# MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI SCHUKO WYŁĄCZNIK

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	247057	<b>Dimensions (H/W/T/S) [mm]:</b>	300/400/100
<b>Light source:</b>	LED module	<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	32	<b>Ingress protection:</b>	IP54
<b>Rated power of the luminaire [W]:</b>	32	<b>Plug type:</b>	UNI-SCHUKO
<b>Supply voltage [V]:</b>	220-240	<b>Socket type:</b>	SCHUKO
<b>Luminous flux [lm]:</b>	4300	<b>Sockets:</b>	2
<b>Energy efficiency class:</b>	D	<b>Cable length [m]:</b>	5
<b>Electrical protection class:</b>	I	<b>Switch:</b>	yes
<b>Colour temperature [K]:</b>	4000	<b>Net weight [kg]:</b>	2.900
<b>Beam angle [°]:</b>	120	<b>Category type:</b>	workplace floodlights
<b>Diffuser material:</b>	PC	<b>ETIM class:</b>	EC000346
<b>Diffuser type:</b>	frozen	<b>Technical Warranty:</b>	5
<b>Material of the body:</b>	PP	<b>CE certificate:</b>	<a href="#">175/2023</a>
<b>Colour of the body:</b>	grey	<b>Manual:</b>	<a href="#">Download PDF</a>

# MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI SCHUKO WYŁĄCZNIK

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 18 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 175/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl