

# MAGNUM FUTURE LITE 32W I KL. OCHR. Z GNIAZDEM SCHUKO

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	406225
<b>Ingress protection:</b>	IP54
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	32
<b>Colour temperature [K]:</b>	4000
<b>Luminous flux [lm]*:</b>	3600
<b>Supply voltage [V]:</b>	220-240
<b>Electrical protection class:</b>	I
<b>Material of the body:</b>	PP
<b>Colour of the body:</b>	green

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

## APPLICATION

The luminaire will provide precise illumination of the workplace.

# MAGNUM FUTURE LITE 32W I KL. OCHR. Z GNIAZDEM SCHUKO

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	32	Material of the body:	PP
Light source:	LED module	Colour of the body:	green
Colour temperature [K]:	4000	Dimensions (H/W/T/S) [mm]:	300/400/100
Luminous flux [lm]:	3600	Ingress protection:	IP54
Plug type:	UNI-SCHUKO	Impact resistance:	IK10
Supply voltage [V]:	220-240	Wire type:	H07RN-F 2×1,0mm
Socket type:	SCHUKO	Net weight [kg]:	2.700
Electrical protection class:	I	Index:	406225
Sockets:	1	Category type:	workplace floodlights
Beam angle [°]:	120	Warranty [years]:	2
Diffuser material:	PC	Manual:	<a href="#">Download PDF</a>
Cable length [m]:	3	Energy efficiency class:	E
Diffuser type:	frozen	ETIM class:	EC000346

# MAGNUM FUTURE LITE 32W I KL. OCHR. Z GNIAZDEM SCHUKO

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 139/2023