

# MAGNUM FUTURE LITE 50W I KL. OCHR. Z GNIAZDEM DK

DETAILED CARD



## TECHNICAL PARAMETERS

|                                     |         |
|-------------------------------------|---------|
| <b>Index:</b>                       | 406263  |
| <b>Ingress protection:</b>          | IP44    |
| <b>Impact resistance:</b>           | IK10    |
| <b>Nominal power [W]:</b>           | 50      |
| <b>Colour temperature [K]:</b>      | 4000    |
| <b>Luminous flux [lm]*:</b>         | 5500    |
| <b>Supply voltage [V]:</b>          | 220-240 |
| <b>Electrical protection class:</b> | I       |
| <b>Material of the body:</b>        | PP      |
| <b>Colour of the body:</b>          | green   |

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

## APPLICATION

The family of durable and handy MAGNUM FUTURE LED XL luminaires has been designed to illuminate larger areas.

# MAGNUM FUTURE LITE 50W I KL. OCHR. Z GNIAZDEM DK

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                              |            |                            |                              |
|------------------------------|------------|----------------------------|------------------------------|
| Nominal power [W]:           | 50         | Material of the body:      | PP                           |
| Light source:                | LED module | Colour of the body:        | green                        |
| Colour temperature [K]:      | 4000       | Ingress protection:        | IP44                         |
| Luminous flux [lm]:          | 5500       | Dimensions (H/W/T/S) [mm]: | 300/480/75                   |
| Plug type:                   | DK         | Impact resistance:         | IK10                         |
| Supply voltage [V]:          | 220-240    | Net weight [kg]:           | 3.400                        |
| Socket type:                 | DK         | Index:                     | 406263                       |
| Electrical protection class: | I          | Category type:             | workplace floodlights        |
| Sockets:                     | 1          | Warranty [years]:          | 2                            |
| Beam angle [°]:              | 120        | Manual:                    | <a href="#">Download PDF</a> |
| Cable length [m]:            | 3          | Energy efficiency class:   | E                            |
| Diffuser material:           | PC         | ETIM class:                | EC000346                     |
| Diffuser type:               | frozen     |                            |                              |

# MAGNUM FUTURE LITE 50W I KL. OCHR. Z GNIAZDEM DK

DETAILED CARD

## ACCESSORIES AVAILABLE

| index  | Name                                       |
|--------|--|
| 000737 | FUTURE STAND Tripod with Click Head System |
| 000720 | Standard tripod                            |



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 139/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl