

# DIONE LED PLUS ASYMMETRIC DP 3200LM 840 IP65 I KL. OPAL WHITE VANDALPROOF 32W

DETAILED CARD



## TECHNICAL PARAMETERS

|                          |        |
|--------------------------|--------|
| Index:                   | 940682 |
| Nominal power [W]:       | 32     |
| Luminous flux [lm]*:     | 3200   |
| Colour temperature [K]:  | 4000   |
| SDCM:                    | 3      |
| Energy efficiency class: | E      |
| Material of the body:    | ABS    |
| Diffuser material:       | PC     |
| Diffuser type:           | OPAL   |

## CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel and asymmetrical light distribution. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

## APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.


# DIONE LED PLUS ASYMMETRIC DP 3200LM 840 IP65 I KL. OPAL WHITE VANDALPROOF 32W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |            |                                          |                                                                                   |
|-----------------------------------|------------|------------------------------------------|-----------------------------------------------------------------------------------|
| Index:                            | 940682     | Ingress protection:                      | IP65                                                                              |
| Light source:                     | LED module | Working temperature [°C]:                | from -20 to +35                                                                   |
| Nominal power [W]:                | 32         | Dimensions of single box [mm]:           | 340/340/115                                                                       |
| Rated power of the luminaire [W]: | 33         | Net weight [kg]:                         | 43831                                                                             |
| Supply voltage [V]:               | 220-240    | Warranty [years]:                        | 5                                                                                 |
| Frequency [Hz]:                   | 50 - 60    | Permeability factor of the diffuser:     | 0.73                                                                              |
| Luminous flux [lm]:               | 3200       | Category type:                           | bulkheads                                                                         |
| Luminous efficacy [lm/W]:         | 97         | Category of application:                 | educational institutions,<br>commercial facilities                                |
| Energy efficiency class:          | E          | Version:                                 | DP                                                                                |
| Electrical protection class:      | I          | AC voltage range [V]:                    | 198-264                                                                           |
| Colour temperature [K]:           | 4000       | DC voltage range [V]:                    | 176-280                                                                           |
| Color rendering index (Ra) >:     | 80         | LED lifespan L70B50 [h]:                 | 115000                                                                            |
| SDCM:                             | 3          | LED lifespan L80B10 [h]:                 | 75000                                                                             |
| Power factor:                     | 0.90       | LED lifespan L90B10 [h]:                 | 33000                                                                             |
| Beam angle [°]:                   | 120        | Light distribution type:                 | asymmetric                                                                        |
| Surge protection [kV]:            | 1          | Photobiological safety:                  | Risk Group 1 (no photobiological<br>hazard under normal behavioral<br>limitation) |
| Diffuser material:                | PC         | CE certificate:                          | <a href="#">380/2023</a>                                                          |
| Diffuser type:                    | OPAL       | Vandalproof:                             | yes                                                                               |
| Diffuser colour:                  | white      | Warranty [years]:                        | 5                                                                                 |
| Optics material:                  | ABS        | ENEC Certificate:                        | <a href="#">PL BBJ/011/2021/M1/A1</a>                                             |
| Material of the body:             | ABS        | Environmental Product Declaration (EPD): | <a href="#">944/2026</a>                                                          |
| Colour of the body:               | white      | Manual:                                  | <a href="#">Download PDF</a>                                                      |
| Dimensions (H/W/T/S) [mm]:        | 340/115    | Plik LDT:                                | <a href="#">Download</a>                                                          |
| Impact resistance:                | IK10       |                                          |                                                                                   |

## LIGHT CURVES




# DIONE LED PLUS ASYMMETRIC DP 3200LM 840 IP65 I KL. OPAL WHITE VANDALPROOF 32W

DETAILED CARD

## ACCESSORIES AVAILABLE

| index    | Name                                                                          |
|----------|-------------------------------------------------------------------------------|
| 120DL118 | Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant |



Ceiling ring Dione LED steel 1.5 white  
matt RAL 9003 painted vandal  
resistant (120DL118)

Card creation date: 07 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 380/2023