

DIONE LED 1800LM 840 IP65 I KL. RCR OPAL WHITE VANDALPROOF 18W

BULKHEADS

LED

LED |  | IP65 | IK10

TECHNICAL PARAMETERS

Index:	940514
Ingress protection:	IP65
Impact resistance:	IK10
Nominal power [W]:	18
Luminous flux [lm]*:	1800
Colour temperature [K]:	4000
SDCM:	≤ 5
Energy efficiency class:	A
Material of the body:	ABS
Ring material:	Biały

*Tolerance +/- 10%

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED GO! panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Its base and ring are made of UV-resistant material. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel.

The fitting is offered in RCR version:

- sensor used to detect motion; for detection uses microwaves (active sensor).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED 1800LM 840 IP65 I KL. RCR OPAL WHITE

VANDALPROOF 18W

BULKHEADS

LED

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Working temperature [°C]:	from -20 to +25
Nominal power [W]:	18	Motion sensor:	yes
Rated power of the luminaire [W]:	23.20	Dimensions of single box [mm]:	340/340/115
Frequency [Hz]:	50-60	Net weight of the luminaire [kg]:	43831
Luminous flux [lm]:	1800	Gross weight of the luminaire [kg]:	46753
Luminous efficacy [lm/W]:	73	Permeability factor of the diffuser:	0.73
Energy efficiency class:	A	Index:	940514
Electrical protection class:	I	EAN:	950032
Colour temperature [K]:	4000	Category type:	bulkheads
Colour rendering index:	>80	AC voltage range [V]:	230
SDCM:	≤ 5	Light distribution type:	open space
Power factor:	0.90	LED lifespan L70B50 [h]:	110000
Beam angle [°]:	120	LED lifespan L80B20 [h]:	80000
Diffuser material:	PC	LED lifespan L90B10 [h]:	40000
Diffuser type:	OPAL	Optics material:	ABS
Diffuser colour:	white	Vandalproof:	yes
Material of the body:	ABS		
Colour of the body:	white		
Ring material:	Biały		
Ring colour:	340/115		
Dimensions [mm]:	140		
Mounting dimensions [mm]:	IK10		
Impact resistance:	IK10		
Ingress protection:	IP65		

*Tolerance +/- 10%

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2020-07-01



Lena Lighting S.A.
ul. Kórnicka 52
63-000 Środa Wielkopolska

tel. +48 61 28 60 300
e-mail: office@lenalighting.pl
www.lenalighting.pl



The luminaire complies with the EU ROHS Directive 2011/65/UE



This product is a subject to electric and electronic waste equipment regulations (WEEE).

