

DIONE LED PLUS 3700LM 840 IP65 I KL. OPAL WHITE 30W

BULKHEADS

LED



LED |  | IP65 |  | IK10 |  | CE

TECHNICAL PARAMETERS

Index:	943300
Ingress protection:	IP65
Impact resistance:	IK10
Nominal power [W]:	30
Luminous flux [lm]*:	3700
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	A+
Material of the body:	ABS
Ring material:	ABS

*Tolerance +/- 10%

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED GO! panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Its base and ring are made of UV-resistant material. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS 3700LM 840 IP65 I KL. OPAL WHITE 30W

BULKHEADS

LED

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ingress protection:	IP65
Nominal power [W]:	30	Mounting version:	surface
Rated power of the luminaire [W]:	36	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Dimensions of single box [mm]:	340/340/115
Frequency [Hz]:	50 - 60	Net weight of the luminaire [kg]:	1
Luminous flux [lm]:	3700	Gross weight of the luminaire [kg]:	1.340
Luminous efficacy [lm/W]:	99	Permeability factor of the diffuser:	0.73
Energy efficiency class:	A+	Index:	943300
Electrical protection class:	I	Category type:	bulkheads
Colour temperature [K]:	4000	AC voltage range [V]:	198-264
Colour rendering index:	>80	DC voltage range [V]:	176-280
SDCM:	≤ 3	LED lifespan L70B50 [h]:	115000
Power factor:	0.95	LED lifespan L80B20 [h]:	75000
Beam angle [°]:	120	LED lifespan L90B10 [h]:	35000
Diffuser material:	PC	Light distribution type:	open space
Diffuser type:	OPAL	CE certificate:	168/2019
Diffuser colour:	white	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	ABS	Surge protection [kV]:	1
Colour of the body:	white		
Ring material:	ABS		
Ring colour:	white		
Dimensions [mm]:	∅340/115		
Mounting dimensions [mm]:	140		
Impact resistance:	IK10		

*Tolerance +/- 10%

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2020-08-13



Lena Lighting S.A.
ul. Kórnicka 52
63-000 Środa Wielkopolska

tel. +48 61 28 60 300
e-mail: office@lenalighting.pl
www.lenalighting.pl



The luminaire complies with the EU RoHS Directive 2011/65/UE



This product is a subject to electric and electronic waste equipment regulations (WEEE).



168/2019