

SQ 300 LED PLUS LENS 2300LM 840 IP54 II KL. DALI RCR OPAL RAL9005 (24W) 300MM CORRIDOR

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|--------|
| Index: | 664328 |
| Ingress protection: | IP54 |
| Impact resistance: | IK08 |
| Nominal power [W]: | 24 |
| Luminous flux [lm]*: | 2300 |
| Colour temperature [K]: | 4000 |
| Energy efficiency class: | F |
| Material of the body: | ABS |
| Diffuser material: | PS |
| Diffuser type: | OPAL |

CHARACTERISTICS

SQ 300 LED is a new line of square ceiling lamps. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, thanks to which it is characterized by low weight and high impact resistance (IK08). The diffuser made of PC polycarbonate provides the lamp with excellent lighting properties. Integrated LED module provides low power consumption and all the advantages of modern lamps with an LED source. The PLUS version of the luminaire line is equipped with brand components from recognized global manufacturers. It is characterized by extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

APPLICATION

The surface-mounted lamp for ceiling or wall mounting is intended for both indoor use - in rooms with high humidity, passageways, staircases, and outdoor use as façade lighting.

SQ 300 LED PLUS LENS 2300LM 840 IP54 II KL. DALI RCR OPAL RAL9005 (24W) 300MM CORRIDOR

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|--------------------------------------|---|
| Index: | 664328 | Dimensions of single box [mm]: | 305x305x60 |
| Light source: | LED module | Net weight [kg]: | 1 |
| Nominal power [W]: | 24 | Warranty [years]: | 5 |
| Rated power of the luminaire [W]: | 27 | Category type: | bulkheads |
| Supply voltage [V]: | 220 - 240 | Category of application: | HoReCa, commercial facilities, educational institutions |
| Frequency [Hz]: | 50 - 60 | AC voltage range [V]: | 198 -264 |
| Luminous flux [lm]: | 2300 | LED lifespan L70B50 [h]: | 120000 |
| Luminous efficacy [lm/W]: | 85 | LED lifespan L80B20 [h]: | 80000 |
| Energy efficiency class: | F | LED lifespan L90B10 [h]: | 40000 |
| Electrical protection class: | II | Light distribution type: | open space |
| Colour temperature [K]: | 4000 | SDCM: | ≤ 3 |
| Beam angle [°]: | 120 | Power factor: | 0.92 |
| Diffuser material: | PS | Max load (RCR) [W]: | 400 |
| Diffuser type: | OPAL | Surge protection [kV]: | 1 |
| Diffuser colour: | white | Working temperature [°C]: | from -20 to +35 |
| Optics material: | PMMA | Corridor function: | yes |
| Optics: | lens | Permeability factor of the diffuser: | 0.70 |
| Material of the body: | ABS | DC voltage range [V]: | 176 - 280 |
| Colour of the body: | black | Version: | LENS |
| Dimensions (H/W/T/S) [mm]: | 300/300/58 | Photobiological safety: | RG0 - exempt (no photobiological hazard) |
| Mounting dimensions [mm]: | 210 | Warranty [years]: | 5 |
| Impact resistance: | IK08 | ENEC Certificate: | 0316/ENEC/23 |
| Ingress protection: | IP54 | CE certificate: | 111/2023 |
| Mounting version: | surface | PZH certificate: | B-BK-60212-0479/21 |
| Motion sensor: | yes | Manual: | Download PDF |
| DIMM DALI: | yes | | |

LIGHT CURVES



Card creation date: 17 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 111/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl