

ASTRA LED 2300LM 840 AR1 IP66 II CL. WIRE 0,7M WTYK/GN SP10KV (17W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	663369
Ingress protection:	IP66
Impact resistance:	IK08
Rated power of the luminaire [W]*:	17
Luminous flux [lm]*:	2300
Colour temperature [K]:	4000
SDCM:	≤ 5
Colour rendering index:	> 80
Electrical protection class:	II
Energy efficiency class:	D

CHARACTERISTICS

Streetlight LED fitting with high luminous flux (max 153 lm/W) and an integrated energy-saving LED module. The self-cleaning body made of polypropylene (PP) with fibreglass (GF) and the grip made of aluminium. Thanks to the directional lens (made of PC), the light distribution meets the requirements of PN-EN 13201 lighting class. IP66 ingress protection class and IK08 impact-rating features make this fitting extremely tight and shock-resistant (vandal-resistant). Integrated, step-regulated grip allows to set the fitting by 5 degrees in the range of: -5° to +15° (peak to pole); -15° to +5° (side to boom). Options: any RAL color. RCR sensor controlled by remote control.

APPLICATION

Luminaire applicable to: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and mounting: lateral side entry, post-top mounting. Mounting grip integrated with the fitting.


ASTRA LED 2300LM 840 AR1 IP66 II CL. WIRE 0,7M WTYK/GN SP10KV (17W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	663369	Ingress protection:	IP66
EAN:	6633695905963	Mounting version:	Top, on pole / Side, on boom
Light source:	LED module	Working temperature [°C]:	from -20 to +35
Rated power of the luminaire [W]:	17	Tilt angle adjustment [°]:	-5 to +15 (peak); -15 to +5 (side)
Supply voltage [V]:	220 - 240	Lateral surface (SCx) [m2]:	0.018
Frequency [Hz]:	50 - 60	Wire type:	H07RN-F
Luminous flux [lm]:	2300	Cable length [m]:	0.70
Luminous efficacy [lm/W]:	135	Protection type:	10kV
Energy efficiency class:	D	Net weight [kg]:	1.900
Electrical protection class:	II	Category type:	street lighting
Colour temperature [K]:	4000	LED lifespan L80B20 [h]:	75000
Colour rendering index:	> 80	Light distribution type:	symetryczny/uliczny
SDCM:	≤ 5	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Power factor:	0.90	Surge protection [kV]:	10
Diffuser material:	PC	ULOR:	0%
Diffuser type:	matrix led	Optics:	AR1
Diffuser colour:	transparent	Control:	ON/OFF
Material of the body:	PP+FG	Optics material:	PC
Colour of the body:	gray	Warranty [years]:	5
Dimensions (H/W/T/S) [mm]:	640/233/113	CE certificate:	103/2023
Mounting dimensions [mm]:	ø60	ENEC Certificate:	0324/ENEC/23
Impact resistance:	IK08	Manual:	Download PDF

LIGHT CURVES



ASTRA LED 2300LM 840 AR1 IP66 II CL. WIRE 0,7M WTYK/GN SP10KV (17W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
UL00229	mounting grip 78 mm



wall holder (galvanized) (314049)



wall holder (grey) (314056)



mounting grip 78 mm (UL00229)

Card creation date: 22 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 103/2023