BARIS 40 LED Z 3900LM PLX DALI I KL. IP44 1421 MM 830 BLACK 46W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	319938
Rated power of the luminaire [W]*:	46
Luminous flux [lm]*:	3900
Colour temperature [K]:	3000
Ingress protection:	IP44
Energy efficiency class:	F
Material of the body:	aluminium
Colour of the body:	black
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). The optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All BARIS 40 LED suspended luminaires to have 1.2m long slings in a set with a box.

APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms. Wall lamps are intended, among others for use in corridors, passageways as well as sanitary rooms and bathrooms, where IP44 class is required

BARIS 40 LED Z 3900LM PLX DALI I KL. IP44 1421 MM 830 BLACK 46W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	319938
EAN:	5905963319938
Light source:	LED
Rated power of the luminaire [W]:	46
Nominal power [W]:	42
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	3900
Luminous efficacy [lm/W]:	85
Energy efficiency class:	F
Electrical protection class:	I
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Diffuser material:	PC
Diffuser type:	OPAL
Diffuser colour:	white
Material of the body:	aluminium
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	53/40/1421

Mounting dimensions [mm]:	1310
Ingress protection:	IP44
Mounting version:	suspended
Net weight [kg]:	1.850
Category type:	luminaires and linear systems
AC voltage range [V]:	220 - 240
LED lifespan L70B50 [h]:	116000
LED lifespan L80B10 [h]:	73000
LED lifespan L90B10 [h]:	35000
Product line:	1421
DIMM DALI:	yes
Impact resistance:	IK06
Warranty [years]:	5
CE certificate:	237/2023
ENEC Certificate:	PL BBJ/004/2022/M1/A1
Manual:	Download PDF
Environmental Product Declaration (EPD):	852/2025
Category of application:	office lighting
ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018

LIGHT CURVES



Card creation date: 13 October 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 237/2023

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl