

BARIS 40 LED Z 3450LM PRM I IP44 1140 MM 840 ANODE CO 33W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	454240
Rated power of the luminaire [W]*:	33
Luminous flux [lm]*:	3450
Colour temperature [K]:	4000
Ingress protection:	IP44
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	grey
Diffuser material:	PC
Diffuser type:	PRM

CHARACTERISTICS

Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). The optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All BARIS 40 LED suspended luminaires to have 1.2m long slings in a set with a box.

APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms. Wall lamps are intended, among others for use in corridors, passageways as well as sanitary rooms and bathrooms, where IP44 class is required

BARIS 40 LED Z 3450LM PRM I IP44 1140 MM 840 ANODE CO 33W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	454240	Dimensions (H/W/T/S) [mm]:	53/40/1140
EAN:	4542405905963	Mounting dimensions [mm]:	1029
Light source:	LED	Ingress protection:	IP44
Rated power of the luminaire [W]:	33	Mounting version:	suspended
Nominal power [W]:	28	Net weight [kg]:	1.480
Frequency [Hz]:	50 - 60	Category type:	luminaires and linear systems
Luminous flux [lm]:	3450	AC voltage range [V]:	220 - 240
Luminous efficacy [lm/W]:	105	LED lifespan L70B50 [h]:	109000
Energy efficiency class:	E	LED lifespan L80B10 [h]:	69000
Electrical protection class:	I	LED lifespan L90B10 [h]:	34000
Colour temperature [K]:	4000	Impact resistance:	IK06
Color rendering index (Ra) >:	80	Warranty [years]:	5
SDCM:	3	CE certificate:	237/2023
Power factor:	0.93	ENEC Certificate:	PL BB/J/004/2022/M1/A1
Diffuser material:	PC	PZH certificate:	B-BK-60212-0109/21
Diffuser type:	PRM	Manual:	Download PDF
Diffuser colour:	transparent	Environmental Product Declaration (EPD):	852/2025
Material of the body:	aluminium	Category of application:	office lighting
Colour of the body:	grey		

LIGHT CURVES



Card creation date: 24 July 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 237/2023

 **LENA**
LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl