

BARIS 40 LED BRACKET 1600LM PRM DALI I IP44 579 MM 830 BLACK 16W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|-----------------------|
| Rated power of the luminaire [W]*: | 16 |
| Luminous flux [lm]*: | 1600 |
| Colour temperature [K]: | 3000 |
| Ingress protection: | IP44 |
| Energy efficiency class: | E |
| Material of the body: | aluminium |
| Colour of the body: | black |
| Diffuser material: | PS |
| Diffuser type: | PRM |
| Mounting version: | surface, wall mounted |

CHARACTERISTICS

A luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). Optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy.

APPLICATION

The unique design predisposes these luminaires to illuminate: offices, conference rooms, and other representative spaces, in offices, passageways, sanitary rooms, and bathrooms (wall lamps), in public utility buildings.

Versions marked "VD" are only intended for use in traffic zones and corridors inside buildings included in Table 5.1 of EN12464.

BARIS 40 LED BRACKET 1600LM PRM DALI I IP44 579 MM 830 BLACK 16W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|--------------------------------|---------------------------------------|
| Index: | 455520 | Mounting dimensions [mm]: | 165 |
| EAN: | 4555205905963 | Ingress protection: | IP44 |
| Light source: | LED | Mounting version: | surface, wall mounted |
| Rated power of the luminaire [W]: | 16 | DIMM DALI: | yes |
| Nominal power [W]: | 14 | Dimensions of single box [mm]: | 76/56/595 |
| Frequency [Hz]: | 50 - 60 | Number on the palette [pcs]: | 80 |
| Luminous flux [lm]: | 1600 | Net weight [kg]: | 0.870 |
| Luminous efficacy [lm/W]: | 95 | Category type: | battens |
| Energy efficiency class: | E | AC voltage range [V]: | 220 - 240 |
| Electrical protection class: | I | LED lifespan L70B50 [h]: | 108500 |
| Colour temperature [K]: | 3000 | LED lifespan L80B20 [h]: | 68500 |
| Colour rendering index: | >80 | LED lifespan L90B10 [h]: | 33000 |
| SDCM: | <3 | Flicker index: | 0.060 |
| Diffuser material: | PS | Impact resistance: | IK03 |
| Diffuser type: | PRM | Warranty [years]: | 5 |
| Diffuser colour: | transparent | CE certificate: | 240/2023 |
| Material of the body: | aluminium | ENEC Certificate: | PL BBJ/012/2021/M1/A1 |
| Colour of the body: | black | PZH certificate: | B-BK-60212-0109/21 |
| Dimensions (H/W/T/S) [mm]: | 53/71/579 | Manual: | Download PDF |

LIGHT CURVES



Card creation date: 08 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 240/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl