

# GIANT LED EVO 33000LM GRAY WITH PL-FR SOCKETS

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	901263
<b>Light source:</b>	LED module
<b>Rated power of the luminaire [W]*:</b>	227
<b>Luminous flux [lm]*:</b>	33144
<b>Colour temperature [K]:</b>	4000
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	MAT
<b>Diffuser colour:</b>	white
<b>Colour of the body:</b>	grey
<b>Dimensions (H/W/T/S) [mm]:</b>	740/420/320

## CHARACTERISTICS

Lightweight and very powerful portable LED floodlight for professional use. Provides even and stable directional illumination. The lamp is made of impact-resistant polypropylene (PP). The anti-glare diffuser made of polycarbonate (PC), despite its matte surface, transmits up to 80% of the light emitted by the LED. It has an ergonomic carrying handle. Standard: rubber cable H07RN-F 3×1.5mm<sup>2</sup> (5m). With a variety of functions, the lamp is ideal for illuminating any workplace. The high luminous flux and the maximum degree of impact resistance are particularly important in the lighting of construction sites or in the work of services intervening at various emergencies. A high degree of waterproofness allows its use in the harshest weather conditions. Its light weight makes it easy to use for workplace lighting in industrial halls or finishing work.

## APPLICATION

Temporary lighting for construction site, finishing works, outdoor earthworks, road and highway repair, Especially useful for mobile services , emergency services, police, military, firefighters, construction crews, electricians, railroad repair, etc.

# GIANT LED EVO 33000LM GRAY WITH PL-FR SOCKETS

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	901263	<b>Power factor:</b>	0.99
<b>Rated power of the luminaire [W]:</b>	227	<b>Diffuser material:</b>	PC
<b>EAN:</b>	5905963901263	<b>Diffuser type:</b>	MAT
<b>Luminous flux [lm]:</b>	33144	<b>Diffuser colour:</b>	white
<b>Light source:</b>	LED module	<b>Colour of the body:</b>	grey
<b>Colour temperature [K]:</b>	4000	<b>Dimensions (H/W/T/S) [mm]:</b>	740/420/320
<b>Ingress protection:</b>	IP54	<b>Impact resistance:</b>	IK10
<b>Socket type:</b>	PL-FR	<b>Sockets:</b>	2
<b>Plug type:</b>	UNI-SCHUKO	<b>Wire type:</b>	H07RN- 3x1,5mm <sup>2</sup>
<b>Supply voltage [V]:</b>	230	<b>Cable length [m]:</b>	5
<b>Frequency [Hz]:</b>	50	<b>Net weight [kg]:</b>	7.700
<b>Luminous efficacy [lm/W]:</b>	137	<b>Warranty [years]:</b>	5
<b>Energy efficiency class:</b>	C	<b>Additional accessories:</b>	000393
<b>Electrical protection class:</b>	I	<b>CE certificate:</b>	<a href="#">125/2023</a>
<b>Colour rendering index:</b>	>80	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>SDCM:</b>	≤ 3		

# GIANT LED EVO 33000LM GRAY WITH PL-FR SOCKETS

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
000300	Adapter plate with click function for mounting the Giant Luminaire on the tripod
000294	Steel tripod 3 m



Steel tripod 3 m (000294)

Card creation date: 23 November 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 125/2023