

BARIS 40 LED N 4700LM UGR DALI I CL. IP20 1421 MM 830 ANODE CO 44W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	459993
Rated power of the luminaire [W]*:	44
Luminous flux [lm]*:	4700
Colour temperature [K]:	3000
Ingress protection:	IP20
UGR (4H8H):	17.5 - 19.5
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	grey
Diffuser material:	PMMA

CHARACTERISTICS

Luminaires BARIS 40 LED UGR was created to provide maximum comfort and efficiency. A UGR (Unified Glare Rating) of less than 19 minimizes the effect of glare affecting well-being, reducing fatigue and fewer mistakes. Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). Optical system in the form of an opal cover. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All BARIS 40 LED suspended luminaires have 1.2m long slings in a set with a box.

APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms.

BARIS 40 LED N 4700LM UGR DALI I CL. IP20 1421 MM 830 ANODE CO 44W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	459993	Diffuser colour:	transparent
EAN:	5905963459993	Optics:	raster UGR
Category of application:	office lighting	Material of the body:	aluminium
Rated power of the luminaire [W]:	44	Colour of the body:	grey
Luminous flux [lm]:	4700	Dimensions (H/W/T/S) [mm]:	53/40/1421
Supply voltage [V]:	220 - 240	Ingress protection:	IP20
Frequency [Hz]:	50 - 60	Impact resistance:	IK03
Luminous efficacy [lm/W]:	108	Mounting version:	surface
Energy efficiency class:	E	Net weight [kg]:	1.690
Electrical protection class:	I	DIMM DALI:	yes
Colour temperature [K]:	3000	UGR (4H8H):	17.5 - 19.5
Color rendering index (Ra) >:	80	Working temperature [°C]:	from 0 to +35
SDCM:	3	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L70B50 [h]:	116000	Warranty [years]:	5
LED lifespan L80B10 [h]:	73000	CE certificate:	239/2023
LED lifespan L90B10 [h]:	35000	ENEC Certificate:	PL BBJ/003/2022/M1/A1
Diffuser material:	PMMA	Environmental Product Declaration (EPD):	852/2025
Diffuser type:	transparent	Manual:	Download PDF

LIGHT CURVES

