


ELEGANTE SYSTEM LED M 1123MM 1400LM OPAL DALI IP44 840 (16W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	388224
Ingress protection:	IP44/20
Impact resistance:	IK04
Nominal power [W]:	16
Luminous flux [lm]*:	1400
Colour temperature [K]:	4000
SDCM:	3
Energy efficiency class:	F
Material of the body:	aluminium
Colour of the body:	silver

CHARACTERISTICS

ELEGANTE LED SYSTEM is a modern office fixture designed for flush mounting. It provides a combination of high light parameters and a modern decorative effect. The optical design has been designed using an iridescent diaphragm with high permeability and uniform light distribution. Available system switches allow for the design of concealed light lines in various configurations (T, X, L). The advantage of the system's roofs is the lampshade without connections to max. length 25m.

There is also a version of individual fittings.

Available 2 power options - to connect as part of:

- 16W i 8W,
- 30W i 15W.

Assembly should be carried out by qualified person.

Please feel free to contact our lighting designers.

APPLICATION

The luminaire is dedicated for internal use. For use in office and commercial facilities, in particular in representative rooms.


ELEGANTE SYSTEM LED M 1123MM 1400LM OPAL DALI IP44 840 (16W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ingress protection:	IP44/20
Nominal power [W]:	16	Mounting version:	recessed
Rated power of the luminaire [W]:	16.19	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	DIMM DALI:	yes
Frequency [Hz]:	50 - 60	Through wiring:	5x2.5
Source luminous flux [lm]*:	2446	Net weight [kg]:	2.400
Luminous flux [lm]:	1400	Gross weight [kg]:	2.800
Luminous efficacy [lm/W]:	86	Index:	388224
Energy efficiency class:	F	EAN:	5905963388224
Electrical protection class:	I	Category type:	luminaires and linear systems
Colour temperature [K]:	4000	Version:	middle module
Color rendering index (Ra) >:	80	Product line:	SYSTEM 16W/8W
SDCM:	3	LED lifespan L80B10 [h]:	73000
Power factor:	0.92	LED lifespan L90B10 [h]:	36000
LED lifespan L70B50 [h]:	115000	Light distribution type:	open space
Diffuser material:	PC	Kolejność:	B
Diffuser colour:	white	ETIM class:	EC000282
Material of the body:	aluminium	CE certificate:	244/2023
Colour of the body:	silver	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Dimensions (H/W/T/S) [mm]:	1123/90/65	Warranty [years]:	5
Mounting dimensions [mm]:	1123/55	Manual:	Download PDF
Impact resistance:	IK04	Plik LDT:	Download

LIGHT CURVES



ELEGANTE SYSTEM LED M 1123MM 1400LM OPAL DALI IP44 840 (16W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
81000945	ELEGANTE LED SYSTEM - OPAL diffuser - 1 rm (max 25 rm)
388736	ELEGANTE SYSTEM LED end set
388743	ELEGANTE SYSTEM LED gniazdo 3 polowe
388750	ELEGANTE SYSTEM LED gniazdo 5 polowe
388767	ELEGANTE SYSTEM LED wtyk 3 polowy
388774	ELEGANTE SYSTEM LED wtyk 5 polowy
388729	ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m



ELEGANTE SYSTEM LED gniazdo 3 polowe (388743)



ELEGANTE SYSTEM LED gniazdo 5 polowe (388750)



ELEGANTE SYSTEM LED wtyk 3 polowy (388767)



ELEGANTE SYSTEM LED wtyk 5 polowy (388774)



ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m (388729)

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 244/2023