

UV-C STERILON FLOW 72W

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	72
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Material of the body:	carbon steel
Dimensions (H/W/T/S) [mm]:	724/160/160
Ingress protection:	IP20
Mounting version:	detached
Flow air disinfection function:	yes
Max volume of the disinfected room [m ³]:	75
Direct surface disinfection function:	yes

CHARACTERISTICS

UV-C STERILON FLOW 72W luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, fungi from the surface or destroying the DNA or RNA of any exposed microorganisms. It is available as dual-function products.

APPLICATION

Luminaires are recommended for use in service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.

UV-C STERILON FLOW 72W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	240416	Type of light:	ultraviolet UV-C
Category type:	bactericidal and virucidal lamps	Protection against opening:	yes
Product line:	UV-C STERILON	Service life of the UV-C radiation source [h]:	9000
Light source:	UV-C	Noise intensity [dB]:	42
Nominal power [W]:	72	Internal element emitting UV-C radiation [W]:	2x36
Supply voltage [V]:	220 - 240	EAN:	5905963240416
Electrical protection class:	I	Frequency [Hz]:	50 - 60
Exchangeable source:	yes	Luminous efficacy [lm/W]:	2.40
Material of the body:	carbon steel	Light colour:	violet
Colour of the body:	white/silver	LED lifespan L70B50 [h]:	9000
Dimensions (H/W/T/S) [mm]:	724/160/160	Working temperature [°C]:	from -20 to +45
Ingress protection:	IP20	Operating mode:	no
Mounting version:	detached	Control:	yes
Version:	dual-purpose	Master/slave:	no
Plug type:	UNI-SCHUKO	Through wiring:	no
Cable length [m]:	3	Protection type:	yes
Switch:	yes	Number in carton box [pcs]:	1
Total power consumption [W]:	82	Number on the palette [pcs]:	28
UV-C wavelength [nm]:	253.70	Direct surface disinfection function:	yes
Dust filter:	yes	Illumination area at a distance of 1 m:	7
Flow air disinfection function:	yes	Warranty [years]:	2
Max volume of the disinfected room [m3]:	75	CE certificate:	324/2023
HEPA filter holder:	yes	PZH certificate:	B-BK-60212-0317/20
Air flow [m3 / h]:	160	Manual:	Download PDF

UV-C STERILON FLOW 72W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
240485	Wall bracket STERILON FLOW 72W
243646	Set of guide wheels Sterilon Flow 72W matt white
243677	HEPA H10 filter - set of 5 only for the Flow model
WSAW347	WSAW347 - SterilOn fan dust filter 115x115 PPM 30 1pkg=3pcs
243639	UV-C protective glasses



Set of guide wheels Sterilon Flow 72W matt white (243646)



HEPA H10 filter - set of 5 only for the Flow model (243677)



UV-C protective glasses (243639)

Card creation date: 22 July 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 324/2023