

# TERRA 2 LED LONG MULTI

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP20
<b>Nominal power [W] - range:</b>	24/36; 40/44/49
<b>Luminous flux of the luminaire [lm] - range:</b>	2100/2800; 3000/4200; 4500/4900/5050; 4800/5200/5400
<b>Colour temperature [K]:</b>	3000; 4000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	A+; B; C
<b>Material of the body:</b>	powder coated steel
<b>Colour of the body:</b>	white gloss; white mat
<b>Beam angle [°]:</b>	90
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

LED luminaire with high total luminous Flux. Made of powder coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface, recessed in modular and suspended. The surface-mounted version uses solutions that enhance the speed and safety of installation. A multitude of versions & dimensions allow to replace worn-out recessed fluorescent luminaires.

The MULTI luminaire version allows individual configuration: thanks to the built-in micoswitch, it is possible to choose one of three settings (nominal power of the fitting [W] / luminous flux of the fitting [lm]).

## APPLICATION

General purpose surface mounted luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

# TERRA 2 LED LONG MULTI

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### TERRA 2 LED LONG MULTI 24/36W

Nominal power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Optics	Colour of the body	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
24/36	3000	2100/2800	HE	white mat	1195/300/32	B	<a href="#">&gt;&gt; 238550</a>
24/36	3000	2100/2800	HE	white gloss	1195/300/32	B	<a href="#">&gt;&gt; 238567</a>
24/36	4000	3000/4200	HE	white mat	1195/300/32	A+	<a href="#">&gt;&gt; 238093</a>
24/36	4000	3000/4200	HE	white gloss	1195/300/32	A+	<a href="#">&gt;&gt; 238109</a>

### TERRA 2 LED LONG MULTI 40/44/49W

Nominal power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Optics	Colour of the body	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
40/44/49	3000	4500/4900/5050	HE	white mat	1195/300/32	C	<a href="#">&gt;&gt; 240027</a>
40/44/49	3000	4500/4900/5050	HE	white gloss	1195/300/32	C	<a href="#">&gt;&gt; 240034</a>
40/44/49	4000	4800/5200/5400	HE	white mat	1195/300/32	A+	<a href="#">&gt;&gt; 240003</a>
40/44/49	4000	4800/5200/5400	HE	white gloss	1195/300/32	A+	<a href="#">&gt;&gt; 240010</a>

Card creation date: 27 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 355/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl