# TERRA 2 LED LONG MULTI

GENERAL CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Ingress protection:** | IP20 |
| **Nominal power [W] - range:** | 24/36; 40/44/49 |
| **Colour temperature [K]:** | 3000; 4000 |
| **Luminous flux of the luminaire [lm] - range:** | 2100/2800; 3000/4200; 4500/4900/5050; 4800/5200/5400 |
| **Color rendering index (Ra) >:** | 80 |
| **SDCM:** | 3 |
| **Energy efficiency class:** | A+; B; C |
| **Electrical protection class:** | II |
| **Material of the body:** | powder coated steel |
| **Colour of the body:** | white gloss; white mat |
| **Optics:** | HE |
| **Mounting version:** | recessed |

## CHARACTERISTICS

LED luminaire with high total luminous Flux. Made of powder coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface, recessed in modular and suspended. The surface-mounted version uses solutions that enhance the speed and safety of installation. A multitude of versions & dimentions allow to replace worn-out recessed fluorescent luminaires.

The MULTI luminaire version allows individual configuration: thanks to the built-in micoswitch, it is possible to choose one of three settings (nominal power of the fitting [W] / luminous flux of the fitting [lm]).

## APPLICATION

General purpose surface mounted luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

# TERRA 2 LED LONG MULTI

GENERAL CARD

## AVAILABLE VERSIONS

Click index >>, to see details

TERRA 2 LED LONG MULTI 24/36W

| Nominal power [W] - range | Colour temperature [K] | Luminous flux of the luminaire [lm] - range | Optics | Colour of the body | Dimensions (H/W/T/S) [mm] | Index |
|---|---|---|---|---|---|---|
| 24/36 | 3000 | 2100/2800 | HE | white mat | 1195/300/32 | >> 238550 |
| 24/36 | 3000 | 2100/2800 | HE | white gloss | 1195/300/32 | >> 238567 |
| 24/36 | 4000 | 3000/4200 | HE | white mat | 1195/300/32 | >> 238093 |
| 24/36 | 4000 | 3000/4200 | HE | white gloss | 1195/300/32 | >> 238109 |

TERRA 2 LED LONG MULTI 40/44/49W

| Nominal power [W] - range | Colour temperature [K] | Luminous flux of the luminaire [lm] - range | Optics | Colour of the body | Dimensions (H/W/T/S) [mm] | Index |
|---|---|---|---|---|---|---|
| 40/44/49 | 3000 | 4500/4900/5050 | HE | white mat | 1195/300/32 | >> 240027 |
| 40/44/49 | 3000 | 4500/4900/5050 | HE | white gloss | 1195/300/32 | >> 240034 |
| 40/44/49 | 4000 | 4800/5200/5400 | HE | white mat | 1195/300/32 | >> 240003 |
| 40/44/49 | 4000 | 4800/5200/5400 | HE | white gloss | 1195/300/32 | >> 240010 |



The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 355/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl