

TERRA 2 LED LONG MULTI

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Nominal power [W] - range:	24/36; 40/44/49
Luminous flux of the luminaire [lm] - range:	2100/2800; 3000/4200; 4500/4900/5050; 4800/5200/5400
Colour temperature [K]:	3000; 4000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	A+; B; C
Material of the body:	powder coated steel
Colour of the body:	white gloss; white mat
Beam angle [°]:	90
Warranty [years]:	5

CHARACTERISTICS

LED luminaire with high total luminous Flux. Made of powder coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface, recessed in modular and suspended. The surface-mounted version uses solutions that enhance the speed and safety of installation. A multitude of versions & dimensions allow to replace worn-out recessed fluorescent luminaires.

The MULTI luminaire version allows individual configuration: thanks to the built-in microswitch, it is possible to choose one of three settings (nominal power of the fitting [W] / luminous flux of the fitting [lm]).

APPLICATION

General purpose surface mounted luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

TERRA 2 LED LONG MULTI

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

TERRA 2 LED LONG MULTI 24/36W

Nominal power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Optics	Colour of the body	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
24/36	3000	2100/2800	HE	white mat	1195/300/32	B	>> 238550
24/36	3000	2100/2800	HE	white gloss	1195/300/32	B	>> 238567
24/36	4000	3000/4200	HE	white mat	1195/300/32	A+	>> 238093
24/36	4000	3000/4200	HE	white gloss	1195/300/32	A+	>> 238109

TERRA 2 LED LONG MULTI 40/44/49W

Nominal power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Optics	Colour of the body	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
40/44/49	3000	4500/4900/5050	HE	white mat	1195/300/32	C	>> 240027
40/44/49	3000	4500/4900/5050	HE	white gloss	1195/300/32	C	>> 240034
40/44/49	4000	4800/5200/5400	HE	white mat	1195/300/32	A+	>> 240003
40/44/49	4000	4800/5200/5400	HE	white gloss	1195/300/32	A+	>> 240010

Card creation date: 26 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 355/2023