


INDUSTRY IP66 LED MR

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP66
Impact resistance:	IK08
Nominal power [W]:	255.00; 318.00
Luminous flux [lm]*:	40800; 44900; 46800; 47250; 51000
Colour temperature [K]:	4000
Energy efficiency class:	C; D
Material of the body:	aluminium
Colour of the body:	grey
Diffuser material:	glass
Mounting version:	suspended
Dimensions (H/W/T/S) [mm]:	1450/205/125; 1150/205/125;
Optics material:	PC
Warranty [years]:	5

CHARACTERISTICS

INDUSTRY IP66 LED MR is a lamp from the NEXT GEN line, which is a new generation of lamps dedicated to LED technology. The body, made from scratch, made of aluminum profile and subjected to anodization process, provides the lamp with strength and solidity, as well as steel sheet ensuring installation stability. LEDs from a reputable manufacturer and new LED modules have an impact on very high luminous efficacy: up to 148 lm / W. This guarantees that the required lighting level is achieved and that significant energy savings are achieved. The shade is made of UV resistant tempered glass. The combination of materials (aluminum and toughened glass) and a non-dismantled construction with an external connector provides the lamp with high resistance to harsh environmental conditions. The design of the lamp allows you to adjust the lighting angle of the two extreme modules, so there is the possibility of precise lighting of selected parts of the object. Suitable for suspended mounting. Options: any RAL color.

APPLICATION

The multi-purpose LED luminaire has been designed for use in areas requiring high dust and water resistance. It is especially recommended for use in rooms intended for medical and laboratory purposes as well as in industrial premises.

INDUSTRY IP66 LED MR

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

INDUSTRY IP66 LED MR 255W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
255	4000	max 51000	50; 70; 80	1150/205/125; 1450/205/125	A+; A++	>> 663895
255	4000	max 51000	50; 70; 80	1150/205/125; 1450/205/125	A+; A++	>> 663901
255	4000	max 51000	50; 70; 80	1150/205/125; 1450/205/125	A+; A++	>> 663918
255	4000	max 51000	50; 70; 80	1150/205/125; 1450/205/125	A+; A++	>> 552618

INDUSTRY IP66 LED MR 318W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
255	4000	max 51000	50; 70; 80	1150/205/125; 1450/205/125	A+; A++	>> 663925
255	4000	max 51000	50; 70; 80	1150/205/125; 1450/205/125	A+; A++	>> 663932
255	4000	max 51000	50; 70; 80	1150/205/125; 1450/205/125	A+; A++	>> 663949
255	4000	max 51000	50; 70; 80	1150/205/125; 1450/205/125	A+; A++	>> 552625

Card creation date: 28 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 102/2020



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl