

# SITE LITE FUTURE LED

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP44; IP54
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	26.00
<b>Colour temperature [K]:</b>	4000; 5000
<b>Luminous flux [lm]*:</b>	3500
<b>Energy efficiency class:</b>	D
<b>Electrical protection class:</b>	I; II
<b>Material of the body:</b>	PP
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	milky
<b>Colour of the body:</b>	graphite
<b>Dimensions (H/W/T/S) [mm]:</b>	ø198/154;

## CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

Available versions:

- with sockets: PL-FR, DK, SCHUCKO
- without sockets
- with a magnet in the base

## APPLICATION

The luminaire will provide precise illumination of the workplace.

# SITE LITE FUTURE LED

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Plug type	Socket type	Sockets	Cable length [m]	Magnet	Ingress protection	Electrical protection class	Index
26	4000	3500	DK	DK	1	5		IP44	I	<a href="#">&gt;&gt; 621161</a>
26	4000	3500	DK	DK	1	5	yes	IP44	I	<a href="#">&gt;&gt; 621215</a>
26	4000	3500	UNI-SCHUKO			5		IP54	II	<a href="#">&gt;&gt; 621086</a>
26	4000	3500	UNI-SCHUKO			5	yes	IP54	II	<a href="#">&gt;&gt; 621185</a>
26	5000	3500	UNI-SCHUKO			5		IP54	II	<a href="#">&gt;&gt; 621345</a>
26	5000	3500	UNI-SCHUKO			5	yes	IP54	II	<a href="#">&gt;&gt; 621369</a>
26	4000	3500	UNI-SCHUKO	PL-FR	1	5		IP54	I	<a href="#">&gt;&gt; 621093</a>
26	4000	3500	UNI-SCHUKO	PL-FR	1	5	yes	IP54	I	<a href="#">&gt;&gt; 621192</a>
26	4000	3500	UNI-SCHUKO	SCHUKO	1	5		IP54	I	<a href="#">&gt;&gt; 621154</a>
26	4000	3500	UNI-SCHUKO	SCHUKO	1	5	yes	IP54	I	<a href="#">&gt;&gt; 621208</a>
26	5000	3500	UNI-SCHUKO	SCHUKO	1	5		IP54	I	<a href="#">&gt;&gt; 621352</a>
26	5000	3500	UNI-SCHUKO	SCHUKO	1	5	yes	IP54	I	<a href="#">&gt;&gt; 621376</a>

Card creation date: 12 November 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 166/2019



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl