

SITE LITE FUTURE LED BASIC

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44; IP54
Impact resistance:	IK10
Nominal power [W]:	23.00
Colour temperature [K]:	4000; 5000
Luminous flux [lm]*:	2600
Electrical protection class:	I; II
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	milky
Colour of the body:	graphite
Dimensions (H/W/T/S) [mm]:	ø198/154;
Energy efficiency class:	E

CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

Available versions:

- with sockets: PL-FR, DK, SCHUCKO
- without sockets:
- with a magnet in the base

APPLICATION

The luminaire will provide precise illumination of the workplace. It can be used as a workplace luminaire to illuminate workplaces and construction sites. The smaller size and compact design make it more convenient to transport. The luminaire is designed for outdoor use, industrial applications or other applications where the lighting standards allow CRI <80.

SITE LITE FUTURE LED BASIC

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Plug type	Socket type	Sockets	Cable length [m]	Magnet	Electrical protection class	Ingress protection	Index
23	4000	2600	DK	DK	1	3		I	IP44	>> 621031
23	4000	2600	DK	DK	1	3	yes	I	IP44	>> 621079
23	4000	2600	UNI-SCHUKO	PL-FR	1	3		I	IP54	>> 621017
23	4000	2600	UNI-SCHUKO	PL-FR	1	3	yes	I	IP54	>> 621055
23	4000	2600	UNI-SCHUKO	SCHUKO	1	3		I	IP54	>> 621024
23	4000	2600	UNI-SCHUKO	SCHUKO	1	3	yes	I	IP54	>> 621062
23	4000	2600	UNI-SCHUKO			3		II	IP54	>> 621000
23	4000	2600	UNI-SCHUKO			3	yes	II	IP54	>> 621048
23	5000	2600	UNI-SCHUKO	SCHUKO	1	3		I	IP54	>> 621314
23	5000	2600	UNI-SCHUKO	SCHUKO	1	3	yes	I	IP54	>> 621338
23	5000	2600	UNI-SCHUKO			3	yes	II	IP54	>> 621321

Card creation date: 23 September 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 270/2023