FUTURE LINE LED

GENERAL CARD



CHARACTERISTICS

FUTURE LINE LED is a rope light for quick and temporary lighting of the workplace. Available in versions with 3 and 4 luminaires on one rope, it allows to connect them to a maximum of 40 lighting points (10 separate chains). The special shape of luminaires allows for their assembly in construction site conditions (on nails, screws, pipes, scaffolding, etc.) and further free positioning of the light beam. The ropes are equipped with hooks for fixing the cable, multi-purpose mounting brackets and magnets screwed into various places of the luminaire. The length of one lighting chain is 11.5 m (version with 4 luminaires) or 9 m (version with 3 luminaires). Possibility of creating max. 115 m of light line (10x Future Line LED 4x8W luminaire).

Comes as standard: rubber cable H07RN-F 2x1 mm, 23 m initial cable with a plug, 2.5 m between luminaires, 1 m end cable with a socket.

Multi-purpose mounting bracket included.

. .

APPLICATION

An innovative lighting chain designed for fast and universal lighting of workplaces. Its unique shape and functional design allow for express assembly even in non-typical places.

TECHNICAL PARAMETERS

Ingress protection: IP44

Impact resistance: IK09

Nominal power [W]: 24.00; 32.00

Colour temperature [K]: 5000

Luminous flux [lm]*: 2040; 2720

Material of the body: PP

Diffuser material: PC

Diffuser type: milky

Colour of the body: grey

Electrical protection class:

Dimensions (H/W/T/S) [mm]: 141/109/65; 141/109/66; 141/109/67; 141/109/68;

Energy efficiency class:



FUTURE LINE LED

GENERAL CARD

AVAILABLE VERSIONS



FUTURE LINE LED 3x1

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Magnet	Index
24	5000	2040		<u>>> 248573</u>
24	5000	2040	yes	<u>>> 248566</u>

FUTURE LINE LED 4x1

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Magnet	Index
32	5000	2720		<u>>> 248542</u>
32	5000	2720	yes	<u>>> 248559</u>

Card creation date: 03 January 2022



