

FUTURE LINE LED

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|-------------------------------------|--|
| Ingress protection: | IP44 |
| Impact resistance: | IK09 |
| Nominal power [W]: | 24.00; 32.00 |
| Colour temperature [K]: | 5000 |
| Luminous flux [lm]*: | 2040; 2720 |
| Material of the body: | PP |
| Diffuser material: | PC |
| Diffuser type: | milky |
| Colour of the body: | grey |
| Electrical protection class: | II |
| Dimensions (H/W/T/S) [mm]: | 141/109/65; 141/109/66; 141/109/67; 141/109/68; |
| Energy efficiency class: | A |

CHARACTERISTICS

FUTURE LINE LED is a rope light for quick and temporary lighting of the workplace. Available in versions with 3 and 4 luminaires on one rope, it allows to connect them to a maximum of 40 lighting points (10 separate chains). The special shape of luminaires allows for their assembly in construction site conditions (on nails, screws, pipes, scaffolding, etc.) and further free positioning of the light beam. The ropes are equipped with hooks for fixing the cable, multi-purpose mounting brackets and magnets screwed into various places of the luminaire. The length of one lighting chain is 11.5 m (version with 4 luminaires) or 9 m (version with 3 luminaires). Possibility of creating max. 115 m of light line (10x Future Line LED 4x8W luminaire).

Comes as standard: rubber cable H07RN-F 2x1 mm, 23 m initial cable with a plug, 2.5 m between luminaires, 1 m end cable with a socket.

Multi-purpose mounting bracket included.

APPLICATION

An innovative lighting chain designed for fast and universal lighting of workplaces. Its unique shape and functional design allow for express assembly even in non-typical places.

FUTURE LINE LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

FUTURE LINE LED 3x1

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Magnet | Index |
|-------------------|------------------------|---------------------|--------|---------------------------------|
| 24 | 5000 | 2040 | | >> 248573 |
| 24 | 5000 | 2040 | yes | >> 248566 |

FUTURE LINE LED 4x1

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Magnet | Index |
|-------------------|------------------------|---------------------|--------|---------------------------------|
| 32 | 5000 | 2720 | | >> 248542 |
| 32 | 5000 | 2720 | yes | >> 248559 |

Card creation date: 03 January 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 268/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl