

MAGNUM FUTURE LED 32W

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44; IP54; IP55
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32.00
Supply voltage [V]:	220-240; 24; 110; 42-48
Luminous flux [lm]*:	4300
Energy efficiency class:	D
Electrical protection class:	I; II; III
Colour temperature [K]:	4000
Beam angle [°]:	120
Diffuser material:	PC
Diffuser type:	frozen
Material of the body:	PP
Colour of the body:	grey

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle. A rubber cable H07RN-F 3x1.5 mm² (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE LED 32W

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

MAGNUM FUTURE LED 32W 110V

Nominal power [W]	Luminous flux [lm]*	Plug type	Socket type	Sockets	Wire type	Cable length [m]	Switch	Version	Electrical protection class	Ingress protection	Index
32	4300	CEE	CEE	2		5			I	IP44	>> 247231

MAGNUM FUTURE LED 32W 220-240V

Nominal power [W]	Luminous flux [lm]*	Plug type	Socket type	Sockets	Wire type	Cable length [m]	Switch	Version	Electrical protection class	Ingress protection	Index
32	4300	CH				5			II	IP44	>> 247217
32	4300	CH	CH	2		5			I	IP55	>> 247033
32	4300	CH	CH	2		5	yes		I	IP44	>> 247071
32	4300	DK				5			II	IP44	>> 247224
32	4300	DK	DK	2		5			I	IP44	>> 247026
32	4300	DK	DK	2		5	yes		I	IP44	>> 247064
32	4300	UNI-SCHUKO				5			II	IP54	>> 247200
32	4300	UNI-SCHUKO	PL-FR	2		5			I	IP54	>> 247309
32	4300	UNI-SCHUKO	PL-FR	2		5	yes		I	IP54	>> 247040
32	4300	UNI-SCHUKO	SCHUKO	2		5			I	IP54	>> 247019
32	4300	UNI-SCHUKO	SCHUKO	2		5	yes		I	IP54	>> 247057

MAGNUM FUTURE LED 32W 24V

Nominal power [W]	Luminous flux [lm]*	Plug type	Socket type	Sockets	Wire type	Cable length [m]	Switch	Version	Electrical protection class	Ingress protection	Index
32	4300	CEE				5			III	IP44	>> 247262
32	4300	CEE	CEE (2-PIN)	2		5			III	IP44	>> 247279
32	4300	TRAFO				5			III	IP44	>> 247286

MAGNUM FUTURE LED 32W 42-48V

Nominal power [W]	Luminous flux [lm]*	Plug type	Socket type	Sockets	Wire type	Cable length [m]	Switch	Version	Electrical protection class	Ingress protection	Index
32	4300	CEE				5			III	IP44	>> 247248
32	4300	CEE	CEE (2-PIN)	2		5			III	IP44	>> 247255

MAGNUM FUTURE LED 32W

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 13 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: max 178/2023