

MAGNUM FUTURE LITE LED 32W

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44; IP54
Impact resistance:	IK10
Nominal power [W]:	32.00
Colour temperature [K]:	4000
Luminous flux [lm]*:	3600
Supply voltage [V]:	220 - 240; 220-240
Electrical protection class:	I; II
Material of the body:	PP
Colour of the body:	green
Diffuser material:	PC
Diffuser type:	frozen
Dimensions (H/W/T/S) [mm]:	300/400/100;
Energy efficiency class:	E

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE LITE LED 32W

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Plug type	Socket type	Sockets	Cable length [m]	Electrical protection class	Ingress protection	Energy efficiency class	Index
32	4000	3600	DK			3	I	IP44	E	>> 406232
32	4000	3600	DK	DK	1	3	I	IP44	E	>> 406201
32	4000	3600	UNI-SCHUKO			3	II	IP54	E	>> 406249
32	4000	3600	UNI-SCHUKO	PL-FR	1	3	I	IP54	E	>> 406218
32	4000	3600	UNI-SCHUKO	SCHUKO	1	3	I	IP54	E	>> 406225

MAGNUM FUTURE LITE LED 32W

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 139/2023