

# MAGNUM FUTURE LITE LED 50W

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP44; IP54
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	50.00
<b>Colour temperature [K]:</b>	4000
<b>Luminous flux [lm]*:</b>	5500
<b>Supply voltage [V]:</b>	220-240
<b>Electrical protection class:</b>	I; II
<b>Material of the body:</b>	PP
<b>Colour of the body:</b>	green
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	frosted
<b>Dimensions (H/W/T/S) [mm]:</b>	300/480/75;
<b>Energy efficiency class:</b>	E

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

## APPLICATION

The family of durable and handy MAGNUM FUTURE LED XL luminaires has been designed to illuminate larger areas.

# MAGNUM FUTURE LITE LED 50W

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Plug type	Socket type	Sockets	Cable length [m]	Electrical protection class	Ingress protection	Energy efficiency class	Index
50	4000	5500	DK			3	I	IP44	E	<a href="#">&gt;&gt; 406256</a>
50	4000	5500	DK	DK	1	3	I	IP44	E	<a href="#">&gt;&gt; 406263</a>
50	4000	5500	UNI-SCHUKO			3	II	IP54	E	<a href="#">&gt;&gt; 406294</a>
50	4000	5500	UNI-SCHUKO	PL-FR	1	3	I	IP54	E	<a href="#">&gt;&gt; 406270</a>
50	4000	5500	UNI-SCHUKO	SCHUKO	1	3	I	IP54	E	<a href="#">&gt;&gt; 406287</a>

# MAGNUM FUTURE LITE LED 50W

GENERAL CARD

## ACCESSORIES AVAILABLE

index	Name
<a href="#">000737</a>	FUTURE STAND Tripod with Click Head System
<a href="#">000720</a>	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 139/2023