

MAGNUM FUTURE LED XS

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|-------------------------------------|--------------------|
| Ingress protection: | IP44; IP54 |
| Impact resistance: | IK10 |
| Nominal power [W]: | 20.00 |
| Colour temperature [K]: | 4000 |
| Luminous flux [lm]*: | 2300 |
| Supply voltage [V]: | 220-240; 24; 42-48 |
| Electrical protection class: | I; II; III |
| Material of the body: | PP |
| Colour of the body: | grey |
| Diffuser material: | PC |
| Diffuser type: | frozen |
| Dimensions (H/W/T/S) [mm]: | 192/193/123; |
| Energy efficiency class: | D |

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Made of impact-resistant polipropylene (PP). Anti-glare diffuser which transmits up to 80% of the light emitted by the diodes. The smaller size and compact design make it convenient to transport. It is equipped with a movable, multi-position arm also acting as a hook. Multi-purpose mounting bracket included.

It can be mounted on a Future Stand, significantly increasing the range and comfort of use.

APPLICATION

It can be used as a workplace luminaire to illuminate workplaces, workshops or garages.

MAGNUM FUTURE LED XS

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Plug type | Socket type | Sockets | Cable length [m] | Electrical protection class | Ingress protection | Dimensions (H/W/T/S) [mm] | Energy efficiency class | Index |
|-------------------|------------------------|---------------------|------------|-------------|---------|------------------|-----------------------------|--------------------|---------------------------|-------------------------|---------------------------------|
| 20 | 4000 | 2300 | CEE | | | 3 | III | IP44 | 192/193/123 | D | >> 248467 |
| 20 | 4000 | 2300 | TRAFO | | | 3 | III | IP44 | 192/193/123 | D | >> 248474 |
| 20 | 4000 | 2300 | CEE | | | 3 | III | IP44 | 192/193/123 | D | >> 248450 |
| 20 | 4000 | 2300 | DK | | | 3 | II | IP44 | 192/193/123 | D | >> 248481 |
| 20 | 4000 | 2300 | UNI-SCHUKO | | | 3 | II | IP54 | 192/193/123 | D | >> 248351 |
| 20 | 4000 | 2300 | DK | DK | 1 | 3 | I | IP44 | 192/193/123 | D | >> 248498 |
| 20 | 4000 | 2300 | UNI-SCHUKO | PL-FR | 1 | 3 | I | IP54 | 192/193/123 | D | >> 248368 |
| 20 | 4000 | 2300 | UNI-SCHUKO | SCHUKO | 1 | 3 | I | IP54 | 192/193/123 | D | >> 248405 |
| 20 | 4000 | 2300 | TRAFO | | | 3 | III | IP44 | 192/193/123 | D | >> 248740 |
| 20 | 4000 | 2300 | CEE | | | 3 | III | IP44 | 192/193/123 | D | >> 248726 |
| 20 | 4000 | 2300 | DK | | | 3 | II | IP44 | 192/193/123 | D | >> 248757 |
| 20 | 4000 | 2300 | DK | DK | 1 | 3 | I | IP44 | 192/193/123 | D | >> 248764 |
| 20 | 4000 | 2300 | UNI-SCHUKO | PL-FR | 1 | 3 | I | IP54 | 192/193/123 | D | >> 248535 |
| 20 | 4000 | 2300 | UNI-SCHUKO | SCHUKO | 1 | 3 | I | IP54 | 192/193/123 | D | >> 248689 |
| 20 | 4000 | 2300 | CEE | | | 3 | III | IP44 | 192/193/123 | D | >> 248733 |
| 20 | 4000 | 2300 | UNI-SCHUKO | | | 3 | II | IP54 | 192/193/123 | D | >> 248528 |

MAGNUM FUTURE LED XS

GENERAL CARD

ACCESSORIES AVAILABLE

| index | Name |
|------------------------|--|
| 000737 | FUTURE STAND Tripod with Click Head System |
| 000720 | Standard tripod |



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 173/2023