MAGNUM BATTERY L

GENERAL CARD



TECHNICAL PARAMETERS

| Ingress protection: | IP20 |
|------------------------------|-------------|
| Impact resistance: | IK10 |
| Nominal power [W]: | 70.00 |
| Colour temperature [K]: | 4000 |
| Luminous flux [lm]*: | 9250 |
| Supply voltage [V]: | 18 |
| Energy efficiency class: | D |
| Electrical protection class: | III |
| Material of the body: | PP |
| Colour of the body: | grey |
| Diffuser material: | PC |
| Dimensions (H/W/T/S) [mm]: | 300/478/84; |
| Warranty [years]: | 3 |

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC), transmits up to 80% of the light emitted by the diodes. The smaller size and compact design make it convenient to transport. It is equipped with a movable, multi-position arm also acting as a hook It has a switch with 4-step luminous flux control. It can be mounted on a Future Stand, significantly increasing the range and comfort of use. MAGNUM BATTERY L is also available as a set with a capacious, branded and durable battery and charger. The battery is compatible with other Bosch devices. Battery-powered version: Operating modes for battery-based operation: 2Ah Battery: 1000 lm, working time: 5h 3800 lm, working time: 1h 15min 5650 lm, working time: 45min 9250 lm, working time: 25min 5Ah Battery: 1000 lm, working time: 12h

3800 lm, working time: 3h 20min 5650 lm, working time: 2h 9250 lm, working time: 1h 10min

APPLICATION

It can be used as a workplace luminaire to illuminate workplaces, workshops or garages.



MAGNUM BATTERY L

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Battery | Battery capacity [mAh] | Accessories included | Index |
|----------------------|---------------------------|------------------------|--------------|---------------------------|--|------------------------|
| 70 | 4000 | 9250 | | | | <u>>> 249259</u> |
| 70 | 4000 | 9250 | Bosch 18V | 2 | | <u>>> 249266</u> |
| 70 | 4000 | 9250 | Bosch 18V | 2 | 1 x 2Ah battery; stand with CLICK function | <u>>> 249365</u> |
| 70 | 4000 | 9250 | Bosch 18V | 2 | 1 x 2Ah battery; charger GAL 18V-40; stand with CLICK function | <u>>> 249372</u> |
| 70 | 4000 | 9250 | Bosch 18V | 2 | 2 x 2Ah batteries; stand with CLICK function | <u>>> 249389</u> |
| 70 | 4000 | 9250 | Bosch 18V | 2 | 2 x 2Ah batteries; charger GAL 18V-40; stand with CLICK function | <u>>> 249396</u> |



MAGNUM BATTERY L

GENERAL CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|--|
| 000737 | FUTURE STAND Tripod with Click Head System |
| | ACCU BOSCH 18V 2Ah |
| | ACCU BOSCH 18V 5Ah |
| | ACCU CHARGER BOSCH EU 18V 2Ah/5Ah |
| | ACCU CHARGER BOSCH UK 18V 2Ah/5Ah |



FUTURE STAND Tripod with Click Head System (000737)

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

Certificate CE - Nr: 116/2023

X



This product is a subject to electric and electronic waste equipment regulations (WEEE).