# MAGNUM BATTERY M

GENERAL CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Ingress protection:** | IP20 |
| **Impact resistance:** | IK10 |
| **Nominal power [W]:** | 30.00 |
| **Colour temperature [K]:** | 4000 |
| **Luminous flux [lm]*:** | 4050 |
| **Supply voltage [V]:** | 18 |
| **Energy efficiency class:** | D |
| **Electrical protection class:** | III |
| **Material of the body:** | PP |
| **Colour of the body:** | grey |
| **Diffuser material:** | PC |
| **Dimensions (H/W/T/S) [mm]:** | 205/400/82; |
| **Warranty [years]:** | 3 |

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC), transmits up to 80% of the light emitted by the diodes. The smaller size and compact design make it convenient to transport. It is equipped with a movable, multi-position arm also acting as a hook It has a switch with 4-step luminous flux control. It can be mounted on a Future Stand, significantly increasing the range and comfort of use. MAGNUM BATTERY M is also available as a set with a capacious, branded and durable battery and charger. The battery is compatible with other Bosch devices.
Battery-powered version:
Operating modes for battery-based operation:
2Ah Battery:
500 lm, working time: 9h
1850 lm, working time: 2h 30min
2750 lm, working time: 1h 30min
4050 lm, working time: 1h
5Ah Battery:
500 lm, working time: 23h
1850 lm, working time: 6h
2750 lm, working time: 4h
4050 lm, working time: 2h 30min

## APPLICATION

It can be used as a workplace luminaire to illuminate workplaces, workshops or garages.

# MAGNUM BATTERY M

GENERAL CARD

## AVAILABLE VERSIONS

Click index >>, to see details

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Battery | Battery capacity [mAh] | Accessories included | Index |
|---|---|---|---|---|---|---|
| 30 | 4000 | 4050 | | | | >> 249228 |
| 30 | 4000 | 4050 | Bosch 18V | 2 | | >> 249235 |
| 30 | 4000 | 4050 | Bosch 18V | 2 | 1 x 2Ah battery Bosch; stand 2m with CLICK function | >> 249327 |
| 30 | 4000 | 4050 | Bosch 18V | 2 | 1 x 2Ah battery; charger GAL 18V-40; stand with CLICK function | >> 249334 |
| 30 | 4000 | 4050 | Bosch 18V | 2 | 2 x 2Ah batteries; stand with CLICK function | >> 249341 |
| 30 | 4000 | 4050 | Bosch 18V | 2 | 2 x 2Ah batteries; charger GAL 18V-40; stand with CLICK function | >> 249358 |

# MAGNUM BATTERY M

GENERAL CARD

## ACCESSORIES AVAILABLE

| index | Name |
|---|---|
| | ACCU BOSCH 18V 2Ah |
| | ACCU CHARGER BOSCH UK 18V 2Ah/5Ah |
| | ACCU CHARGER BOSCH EU 18V 2Ah/5Ah |
| | ACCU BOSCH 18V 5Ah |
| 000737 | FUTURE STAND Tripod with Click Head System |



FUTURE STAND Tripod with Click Head System (000737)



The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 116/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl