

SWING LED EVO

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP40/20
Nominal power [W]:	8.00 - 29.00
Luminous flux [lm]*:	850 - 3000
Colour temperature [K]:	3000; 4000
Colour rendering index:	>80
Energy efficiency class:	D; E; F; G
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PC
Beam angle [°]:	25; 59x92; 60
Mounting version:	recessed
Working temperature [°C]:	from -20 to +35
Dimensions (H/W/T/S) [mm]:	ø178/163;
Warranty [years]:	5

CHARACTERISTICS

Recessed frameless downlight fitting equipped with modern and energy-saving light source LED. The body made of plastic, steel and aluminium ensures a long-term operation of the fitting. The diffuser made of highly transparent PC guarantees high luminous flux and ensures optimal conditions for the LED operation. Due to the possibility of adjusting the light direction vertically up to 30° and horizontally (turn) up to 355°, four options of diffuser to choose: 60°, 25°, 59°/92°, as well as modern and elegant design, the fitting is suitable for a variety of applications.

APPLICATION

Recessed fitting suitable for mounting in plasterboard ceilings, dedicated for indoor use as a basic or accent lighting. Due to modern and elegant design and the possibility of choosing the optimal light distribution, the fitting is ideal for offices, commercial buildings and passageways.

SWING LED EVO

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

SWING LED EVO 8W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Energy efficiency class	Index
8	3000	850	25	E	>> 094651
8	4000	940	25	E	>> 094606
8	3000	960	59x92	E	>> 094750
8	4000	1060	59x92	D	>> 094705
8	3000	1000	60	E	>> 094552
8	4000	1100	60	D	>> 094507

SWING LED EVO 12W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Energy efficiency class	Index
12	3000	1100	25	F	>> 094668
12	4000	1280	25	E	>> 094613
12	3000	1300	59x92	E	>> 094767
12	4000	1450	59x92	E	>> 094712
12	3000	1350	60	E	>> 094569
12	4000	1500	60	D	>> 094514

SWING LED EVO 17W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Energy efficiency class	Index
17	3000	1550	25	F	>> 094675
17	4000	1700	25	F	>> 094620
17	3000	1750	59x92	F	>> 094774
17	4000	1950	59x92	E	>> 094729
17	3000	1800	60	E	>> 094576
17	4000	2000	60	E	>> 094521

SWING LED EVO 21W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Energy efficiency class	Index
21	3000	1750	25	F	>> 094682
21	4000	1950	25	F	>> 094637
21	3000	2100	59x92	F	>> 094781
21	4000	2300	59x92	E	>> 094736
21	3000	2150	60	F	>> 094583
21	4000	2400	60	E	>> 094538

SWING LED EVO

GENERAL CARD

SWING LED EVO 25W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Energy efficiency class	Index
25	3000	1950	25	G	>> 094699
25	4000	2200	25	F	>> 094644
25	3000	2300	59x92	F	>> 094798
25	4000	2600	59x92	E	>> 094743
25	3000	2400	60	F	>> 094590
25	4000	2700	60	E	>> 094545


SWING LED EVO 29W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Energy efficiency class	Index
29	3000	2200	25	G	>> 094828
29	4000	2500	25	F	>> 094835
29	3000	2600	59x92	F	>> 094804
29	4000	2900	59x92	E	>> 094811
29	3000	2700	60	F	>> 094842
29	4000	3000	60	E	>> 094859


SWING LED EVO

GENERAL CARD


LUMINOUS INTENSITY DISTRIB. CURVE



SWING LED EVO 25



SWING LED EVO 59x92



SWING LED EVO 60

Card creation date: 28 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 351/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl