

MAGNUM HOBBY 50W

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44; IP54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	50.00
Colour temperature [K]:	4000
Luminous flux [lm]*:	5500
Supply voltage [V]:	220-240
Electrical protection class:	I; II
Material of the body:	PP
Colour of the body:	green
Diffuser material:	PC
Diffuser type:	frozen
Dimensions (H/W/T/S) [mm]:	300/480/75;
Warranty [years]:	2

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The family of durable and handy luminaires has been designed to illuminate larger areas.

MAGNUM HOBBY 50W

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Plug type	Socket type	Sockets	Cable length [m]	Electrical protection class	Ingress protection	Index
50	4000	5500	frozen	DK			3	I	IP44	>> 406454
50	4000	5500	frozen	UNI-SCHUKO			3	II	IP54	>> 406492
50	4000	5500	frozen	DK	DK	1	3	I	IP44	>> 406461
50	4000	5500	frozen	UNI-SCHUKO	PL-FR	1	3	I	IP54	>> 406478
50	4000	5500	frozen	UNI-SCHUKO	SCHUKO	1	3	I	IP54	>> 406485

Card creation date: 20 November 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 139/2020



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl