

RQ 160 LED N

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|-----------------------------------|----------------------|
| Ingress protection: | IP33; IP44 |
| Impact resistance: | IK08 |
| Nominal power [W]: | 17.00 |
| Luminous flux [lm]*: | 1700 - 2200 |
| Colour temperature [K]: | 3000; 4000 |
| Colour rendering index: | >80 |
| Energy efficiency class: | D; E; F |
| Material of the body: | ABS |
| Colour of the body: | white |
| Diffuser material: | PC |
| Diffuser type: | MAT; OPAL; PRM |
| Beam angle [°]: | 75; 110; 115 |
| Mounting version: | surface |
| Working temperature [°C]: | from -20 to +35 |
| Dimensions (H/W/T/S) [mm]: | 166/86; 171/97; |
| Warranty [years]: | 5 |
| PZH certificate: | B-BK-60112-0365-2022 |

CHARACTERISTICS

RQ 160 LED N is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.

RQ 160 LED N

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

RQ 160 LED N 17W

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Ingress protection | Dimensions (H/W/T/S) [mm] | Index |
|-------------------|------------------------|---------------------|---------------|--------------------|---------------------------|---------------------------------|
| 17 | 3000 | 1700 | MAT | IP33 | 166/86 | >> 570483 |
| 17 | 3000 | 1700 | MAT | IP44 | 171/97 | >> 573903 |
| 17 | 4000 | 1800 | MAT | IP33 | 166/86 | >> 570339 |
| 17 | 4000 | 1800 | MAT | IP44 | 171/97 | >> 573910 |
| 17 | 3000 | 2100 | PRM | IP33 | 166/86 | >> 570537 |
| 17 | 3000 | 2100 | PRM | IP44 | 171/97 | >> 573941 |
| 17 | 4000 | 2200 | PRM | IP33 | 166/86 | >> 570384 |
| 17 | 4000 | 2200 | PRM | IP44 | 171/97 | >> 573958 |
| 17 | 3000 | 1900 | OPAL | IP33 | 166/86 | >> 570582 |
| 17 | 3000 | 1900 | OPAL | IP44 | 171/97 | >> 573927 |
| 17 | 4000 | 2050 | OPAL | IP33 | 166/86 | >> 570438 |
| 17 | 4000 | 2050 | OPAL | IP44 | 171/97 | >> 573934 |

RQ 160 LED N

GENERAL CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|---|
| 573637 | Suspension RQ160 fi100 white ON/OFF. DALI |

Card creation date: 10 December 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 154/2020; 317/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl