

BARIS 40 LED

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|---|---|
| Rated power of the luminaire [W]*: | 14.00 - 50.00 |
| Luminous flux [lm]*: | 1300 - 5900 |
| Colour temperature [K]: | 3000; 4000 |
| Ingress protection: | IP20; IP44 |
| Impact resistance: | IK06 |
| Material of the body: | aluminium |
| Colour of the body: | black; grey; white |
| Diffuser type: | OPAL; PRM |
| Mounting version: | surface; suspended |
| Dimensions (H/W/T/S) [mm]: | 53/40/1140; 53/40/1421; 53/40/579; 53/40/860 |
| Warranty [years]: | 5 |

CHARACTERISTICS

Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All BARIS 40 LED suspended luminaires to have 1.2m long slings in a set with a box.

APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms. Wall lamps are intended, among others for use in corridors, passageways as well as sanitary rooms and bathrooms, where IP44 class is required

BARIS 40 LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

BARIS 40 LED surface

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Colour of the body | Dimensions (H/W/T/S) [mm] | Ingress protection | DIMM DALI | Mounting version | Index |
|-----------------------------------|------------------------|---------------------|---------------|--------------------|---------------------------|--------------------|-----------|------------------|---------------------------------|
| 14 | 3000 | 1300 | OPAL | grey | 53/40/860 | IP20 | yes | surface | >> 930140 |
| 14 | 3000 | 1300 | OPAL | white | 53/40/860 | IP20 | yes | surface | >> 930126 |
| 14 | 3000 | 1300 | OPAL | black | 53/40/860 | IP20 | yes | surface | >> 930133 |
| 14 | 3000 | 1300 | OPAL | grey | 53/40/860 | IP20 | | surface | >> 925825 |
| 14 | 3000 | 1300 | OPAL | white | 53/40/860 | IP20 | | surface | >> 925801 |
| 14 | 3000 | 1300 | OPAL | black | 53/40/860 | IP20 | | surface | >> 925818 |
| 14 | 4000 | 1400 | OPAL | grey | 53/40/860 | IP20 | yes | surface | >> 925368 |
| 14 | 4000 | 1400 | OPAL | white | 53/40/860 | IP20 | yes | surface | >> 930089 |
| 14 | 4000 | 1400 | OPAL | black | 53/40/860 | IP20 | yes | surface | >> 930096 |
| 14 | 4000 | 1400 | OPAL | grey | 53/40/860 | IP20 | | surface | >> 925511 |
| 14 | 4000 | 1400 | OPAL | white | 53/40/860 | IP20 | | surface | >> 925498 |
| 14 | 4000 | 1400 | OPAL | black | 53/40/860 | IP20 | | surface | >> 925504 |
| 14 | 3000 | 1450 | PRM | grey | 53/40/860 | IP20 | yes | surface | >> 930171 |
| 14 | 3000 | 1450 | PRM | white | 53/40/860 | IP20 | yes | surface | >> 930157 |
| 14 | 3000 | 1450 | PRM | black | 53/40/860 | IP20 | yes | surface | >> 930164 |
| 14 | 3000 | 1450 | PRM | grey | 53/40/860 | IP20 | | surface | >> 925856 |
| 14 | 3000 | 1450 | PRM | white | 53/40/860 | IP20 | | surface | >> 925832 |
| 14 | 3000 | 1450 | PRM | black | 53/40/860 | IP20 | | surface | >> 925849 |
| 14 | 4000 | 1550 | PRM | grey | 53/40/860 | IP20 | yes | surface | >> 925399 |
| 14 | 4000 | 1550 | PRM | white | 53/40/860 | IP20 | yes | surface | >> 930102 |
| 14 | 4000 | 1550 | PRM | black | 53/40/860 | IP20 | yes | surface | >> 930119 |
| 14 | 4000 | 1550 | PRM | grey | 53/40/860 | IP20 | | surface | >> 925603 |
| 14 | 4000 | 1550 | PRM | white | 53/40/860 | IP20 | | surface | >> 925580 |
| 14 | 4000 | 1550 | PRM | black | 53/40/860 | IP20 | | surface | >> 925597 |
| 16 | 3000 | 1300 | OPAL | grey | 53/40/579 | IP20 | yes | surface | >> 319136 |
| 16 | 3000 | 1300 | OPAL | white | 53/40/579 | IP20 | yes | surface | >> 319174 |
| 16 | 3000 | 1300 | OPAL | black | 53/40/579 | IP20 | yes | surface | >> 319211 |
| 16 | 3000 | 1300 | OPAL | grey | 53/40/579 | IP20 | | surface | >> 319112 |
| 16 | 3000 | 1300 | OPAL | white | 53/40/579 | IP20 | | surface | >> 319150 |
| 16 | 3000 | 1300 | OPAL | black | 53/40/579 | IP20 | | surface | >> 319198 |
| 16 | 4000 | 1400 | OPAL | grey | 53/40/579 | IP20 | yes | surface | >> 319129 |
| 16 | 4000 | 1400 | OPAL | white | 53/40/579 | IP20 | yes | surface | >> 319167 |
| 16 | 4000 | 1400 | OPAL | black | 53/40/579 | IP20 | yes | surface | >> 319204 |

BARIS 40 LED

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Colour of the body | Dimensions (H/W/T/S) [mm] | Ingress protection | DIMM DALI | Mounting version | Index |
|-----------------------------------|------------------------|---------------------|---------------|--------------------|---------------------------|--------------------|-----------|------------------|---------------------------------|
| 16 | 4000 | 1400 | OPAL | grey | 53/40/579 | IP20 | | surface | >> 319105 |
| 16 | 4000 | 1400 | OPAL | white | 53/40/579 | IP20 | | surface | >> 319143 |
| 16 | 4000 | 1400 | OPAL | black | 53/40/579 | IP20 | | surface | >> 319181 |
| 16 | 3000 | 1600 | PRM | grey | 53/40/579 | IP20 | yes | surface | >> 455292 |
| 16 | 3000 | 1600 | PRM | white | 53/40/579 | IP20 | yes | surface | >> 455339 |
| 16 | 3000 | 1600 | PRM | black | 53/40/579 | IP20 | yes | surface | >> 455377 |
| 16 | 3000 | 1600 | PRM | grey | 53/40/579 | IP20 | | surface | >> 455278 |
| 16 | 3000 | 1600 | PRM | white | 53/40/579 | IP20 | | surface | >> 455315 |
| 16 | 3000 | 1600 | PRM | black | 53/40/579 | IP20 | | surface | >> 455353 |
| 16 | 4000 | 1700 | PRM | grey | 53/40/579 | IP20 | yes | surface | >> 455285 |
| 16 | 4000 | 1700 | PRM | white | 53/40/579 | IP20 | yes | surface | >> 455322 |
| 16 | 4000 | 1700 | PRM | black | 53/40/579 | IP20 | yes | surface | >> 455360 |
| 16 | 4000 | 1700 | PRM | grey | 53/40/579 | IP20 | | surface | >> 455261 |
| 16 | 4000 | 1700 | PRM | white | 53/40/579 | IP20 | | surface | >> 455308 |
| 16 | 4000 | 1700 | PRM | black | 53/40/579 | IP20 | | surface | >> 455346 |
| 18 | 3000 | 1700 | OPAL | grey | 53/40/1140 | IP20 | | surface | >> 319297 |
| 18 | 3000 | 1700 | OPAL | white | 53/40/1140 | IP20 | | surface | >> 319334 |
| 18 | 3000 | 1700 | OPAL | black | 53/40/1140 | IP20 | | surface | >> 319372 |
| 18 | 4000 | 1850 | OPAL | grey | 53/40/1140 | IP20 | | surface | >> 319280 |
| 18 | 4000 | 1850 | OPAL | white | 53/40/1140 | IP20 | | surface | >> 319327 |
| 18 | 4000 | 1850 | OPAL | black | 53/40/1140 | IP20 | | surface | >> 319365 |
| 18 | 3000 | 2100 | PRM | grey | 53/40/1140 | IP20 | | surface | >> 454134 |
| 18 | 3000 | 2100 | PRM | white | 53/40/1140 | IP20 | | surface | >> 454158 |
| 18 | 3000 | 2100 | PRM | black | 53/40/1140 | IP20 | | surface | >> 454172 |
| 18 | 4000 | 2300 | PRM | grey | 53/40/1140 | IP20 | | surface | >> 454127 |
| 18 | 4000 | 2300 | PRM | white | 53/40/1140 | IP20 | | surface | >> 454141 |
| 18 | 4000 | 2300 | PRM | black | 53/40/1140 | IP20 | | surface | >> 454165 |
| 23 | 3000 | 2100 | OPAL | grey | 53/40/860 | IP20 | yes | surface | >> 930249 |
| 23 | 3000 | 2100 | OPAL | white | 53/40/860 | IP20 | yes | surface | >> 930256 |
| 23 | 3000 | 2100 | OPAL | black | 53/40/860 | IP20 | yes | surface | >> 930263 |
| 23 | 3000 | 2100 | OPAL | grey | 53/40/860 | IP20 | | surface | >> 925924 |
| 23 | 3000 | 2100 | OPAL | white | 53/40/860 | IP20 | | surface | >> 925931 |
| 23 | 3000 | 2100 | OPAL | black | 53/40/860 | IP20 | | surface | >> 925948 |
| 23 | 4000 | 2300 | OPAL | grey | 53/40/860 | IP20 | yes | surface | >> 925641 |
| 23 | 4000 | 2300 | OPAL | white | 53/40/860 | IP20 | yes | surface | >> 930041 |
| 23 | 4000 | 2300 | OPAL | black | 53/40/860 | IP20 | yes | surface | >> 930058 |
| 23 | 4000 | 2300 | OPAL | grey | 53/40/860 | IP20 | | surface | >> 925146 |
| 23 | 4000 | 2300 | OPAL | white | 53/40/860 | IP20 | | surface | >> 925153 |

BARIS 40 LED

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Colour of the body | Dimensions (H/W/T/S) [mm] | Ingress protection | DIMM DALI | Mounting version | Index |
|-----------------------------------|------------------------|---------------------|---------------|--------------------|---------------------------|--------------------|-----------|------------------|---------------------------------|
| 23 | 4000 | 2300 | OPAL | black | 53/40/860 | IP20 | | surface | >> 925160 |
| 23 | 3000 | 2350 | PRM | grey | 53/40/860 | IP20 | yes | surface | >> 930270 |
| 23 | 3000 | 2350 | PRM | white | 53/40/860 | IP20 | yes | surface | >> 930287 |
| 23 | 3000 | 2350 | PRM | black | 53/40/860 | IP20 | yes | surface | >> 930294 |
| 23 | 3000 | 2350 | PRM | grey | 53/40/860 | IP20 | | surface | >> 925955 |
| 23 | 3000 | 2350 | PRM | white | 53/40/860 | IP20 | | surface | >> 925962 |
| 23 | 3000 | 2350 | PRM | black | 53/40/860 | IP20 | | surface | >> 925979 |
| 23 | 4000 | 2500 | PRM | grey | 53/40/860 | IP20 | yes | surface | >> 925672 |
| 23 | 4000 | 2500 | PRM | white | 53/40/860 | IP20 | yes | surface | >> 930065 |
| 23 | 4000 | 2500 | PRM | black | 53/40/860 | IP20 | yes | surface | >> 930072 |
| 23 | 4000 | 2500 | PRM | grey | 53/40/860 | IP20 | | surface | >> 925245 |
| 23 | 4000 | 2500 | PRM | white | 53/40/860 | IP20 | | surface | >> 925252 |
| 23 | 4000 | 2500 | PRM | black | 53/40/860 | IP20 | | surface | >> 925269 |
| 33 | 3000 | 2600 | OPAL | grey | 53/40/1140 | IP20 | | surface | >> 318382 |
| 33 | 3000 | 2600 | OPAL | white | 53/40/1140 | IP20 | | surface | >> 318405 |
| 33 | 3000 | 2600 | OPAL | black | 53/40/1140 | IP20 | | surface | >> 318429 |
| 33 | 4000 | 2800 | OPAL | grey | 53/40/1140 | IP20 | | surface | >> 318375 |
| 33 | 4000 | 2800 | OPAL | white | 53/40/1140 | IP20 | | surface | >> 318399 |
| 33 | 4000 | 2800 | OPAL | black | 53/40/1140 | IP20 | | surface | >> 318412 |
| 33 | 3000 | 3200 | PRM | grey | 53/40/1140 | IP20 | | surface | >> 454318 |
| 33 | 3000 | 3200 | PRM | white | 53/40/1140 | IP20 | | surface | >> 454332 |
| 33 | 3000 | 3200 | PRM | black | 53/40/1140 | IP20 | | surface | >> 454356 |
| 33 | 4000 | 3450 | PRM | grey | 53/40/1140 | IP20 | | surface | >> 454301 |
| 33 | 4000 | 3450 | PRM | white | 53/40/1140 | IP20 | | surface | >> 454325 |
| 33 | 4000 | 3450 | PRM | black | 53/40/1140 | IP20 | | surface | >> 454349 |
| 39 | 3000 | 3400 | OPAL | grey | 53/40/1421 | IP20 | | surface | >> 319655 |
| 39 | 3000 | 3400 | OPAL | white | 53/40/1421 | IP20 | | surface | >> 319693 |
| 39 | 3000 | 3400 | OPAL | black | 53/40/1421 | IP20 | | surface | >> 319730 |
| 39 | 4000 | 3700 | OPAL | grey | 53/40/1421 | IP20 | | surface | >> 319648 |
| 39 | 4000 | 3700 | OPAL | white | 53/40/1421 | IP20 | | surface | >> 319686 |
| 39 | 4000 | 3700 | OPAL | black | 53/40/1421 | IP20 | | surface | >> 319723 |
| 39 | 3000 | 4200 | PRM | grey | 53/40/1421 | IP20 | | surface | >> 454851 |
| 39 | 3000 | 4200 | PRM | white | 53/40/1421 | IP20 | | surface | >> 454875 |
| 39 | 3000 | 4200 | PRM | black | 53/40/1421 | IP20 | | surface | >> 454899 |
| 39 | 4000 | 4550 | PRM | grey | 53/40/1421 | IP20 | | surface | >> 454844 |
| 39 | 4000 | 4550 | PRM | white | 53/40/1421 | IP20 | | surface | >> 454868 |
| 39 | 4000 | 4550 | PRM | black | 53/40/1421 | IP20 | | surface | >> 454882 |
| 39 | 3000 | 3600 | OPAL | grey | 53/40/860 | IP20 | yes | surface | >> 930188 |

BARIS 40 LED

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Colour of the body | Dimensions (H/W/T/S) [mm] | Ingress protection | DIMM DALI | Mounting version | Index |
|-----------------------------------|------------------------|---------------------|---------------|--------------------|---------------------------|--------------------|-----------|------------------|---------------------------------|
| 39 | 3000 | 3600 | OPAL | white | 53/40/860 | IP20 | yes | surface | >> 930195 |
| 39 | 3000 | 3600 | OPAL | black | 53/40/860 | IP20 | yes | surface | >> 930201 |
| 39 | 3000 | 3600 | OPAL | grey | 53/40/860 | IP20 | | surface | >> 925863 |
| 39 | 3000 | 3600 | OPAL | white | 53/40/860 | IP20 | | surface | >> 925870 |
| 39 | 3000 | 3600 | OPAL | black | 53/40/860 | IP20 | | surface | >> 925887 |
| 39 | 4000 | 3900 | OPAL | grey | 53/40/860 | IP20 | yes | surface | >> 925092 |
| 39 | 4000 | 3900 | OPAL | white | 53/40/860 | IP20 | yes | surface | >> 930003 |
| 39 | 4000 | 3900 | OPAL | black | 53/40/860 | IP20 | yes | surface | >> 930010 |
| 39 | 4000 | 3900 | OPAL | grey | 53/40/860 | IP20 | | surface | >> 466809 |
| 39 | 4000 | 3900 | OPAL | white | 53/40/860 | IP20 | | surface | >> 466816 |
| 39 | 4000 | 3900 | OPAL | black | 53/40/860 | IP20 | | surface | >> 466823 |
| 39 | 3000 | 4150 | PRM | grey | 53/40/860 | IP20 | yes | surface | >> 930218 |
| 39 | 3000 | 4150 | PRM | white | 53/40/860 | IP20 | yes | surface | >> 930225 |
| 39 | 3000 | 4150 | PRM | black | 53/40/860 | IP20 | yes | surface | >> 930232 |
| 39 | 3000 | 4150 | PRM | grey | 53/40/860 | IP20 | | surface | >> 925894 |
| 39 | 3000 | 4150 | PRM | white | 53/40/860 | IP20 | | surface | >> 925900 |
| 39 | 3000 | 4150 | PRM | black | 53/40/860 | IP20 | | surface | >> 925917 |
| 39 | 4000 | 4450 | PRM | grey | 53/40/860 | IP20 | yes | surface | >> 925610 |
| 39 | 4000 | 4450 | PRM | white | 53/40/860 | IP20 | yes | surface | >> 930027 |
| 39 | 4000 | 4450 | PRM | black | 53/40/860 | IP20 | yes | surface | >> 930034 |
| 39 | 4000 | 4450 | PRM | grey | 53/40/860 | IP20 | | surface | >> 925009 |
| 39 | 4000 | 4450 | PRM | white | 53/40/860 | IP20 | | surface | >> 925016 |
| 39 | 4000 | 4450 | PRM | black | 53/40/860 | IP20 | | surface | >> 925023 |
| 46 | 3000 | 3900 | OPAL | grey | 53/40/1421 | IP20 | yes | surface | >> 319679 |
| 46 | 3000 | 3900 | OPAL | white | 53/40/1421 | IP20 | yes | surface | >> 319716 |
| 46 | 3000 | 3900 | OPAL | black | 53/40/1421 | IP20 | yes | surface | >> 319754 |
| 46 | 3000 | 3900 | OPAL | grey | 53/40/1421 | IP20 | | surface | >> 318443 |
| 46 | 3000 | 3900 | OPAL | white | 53/40/1421 | IP20 | | surface | >> 318467 |
| 46 | 3000 | 3900 | OPAL | black | 53/40/1421 | IP20 | | surface | >> 318481 |
| 46 | 4000 | 4300 | OPAL | grey | 53/40/1421 | IP20 | yes | surface | >> 319662 |
| 46 | 4000 | 4300 | OPAL | white | 53/40/1421 | IP20 | yes | surface | >> 319709 |
| 46 | 4000 | 4300 | OPAL | black | 53/40/1421 | IP20 | yes | surface | >> 319747 |
| 46 | 4000 | 4300 | OPAL | grey | 53/40/1421 | IP20 | | surface | >> 318436 |
| 46 | 4000 | 4300 | OPAL | white | 53/40/1421 | IP20 | | surface | >> 318450 |
| 46 | 4000 | 4300 | OPAL | black | 53/40/1421 | IP20 | | surface | >> 318474 |
| 46 | 3000 | 4800 | PRM | grey | 53/40/1421 | IP20 | yes | surface | >> 455179 |
| 46 | 3000 | 4800 | PRM | white | 53/40/1421 | IP20 | yes | surface | >> 455216 |
| 46 | 3000 | 4800 | PRM | black | 53/40/1421 | IP20 | yes | surface | >> 455254 |

BARIS 40 LED

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Colour of the body | Dimensions (H/W/T/S) [mm] | Ingress protection | DIMM DALI | Mounting version | Index |
|-----------------------------------|------------------------|---------------------|---------------|--------------------|---------------------------|--------------------|-----------|------------------|---------------------------------|
| 46 | 3000 | 4800 | PRM | grey | 53/40/1421 | IP20 | | surface | >> 455155 |
| 46 | 3000 | 4800 | PRM | white | 53/40/1421 | IP20 | | surface | >> 455193 |
| 46 | 3000 | 4800 | PRM | black | 53/40/1421 | IP20 | | surface | >> 455230 |
| 46 | 4000 | 5300 | PRM | grey | 53/40/1421 | IP20 | yes | surface | >> 455162 |
| 46 | 4000 | 5300 | PRM | white | 53/40/1421 | IP20 | yes | surface | >> 455209 |
| 46 | 4000 | 5300 | PRM | black | 53/40/1421 | IP20 | yes | surface | >> 455247 |
| 46 | 4000 | 5300 | PRM | grey | 53/40/1421 | IP20 | | surface | >> 455148 |
| 46 | 4000 | 5300 | PRM | white | 53/40/1421 | IP20 | | surface | >> 455186 |
| 46 | 4000 | 5300 | PRM | black | 53/40/1421 | IP20 | | surface | >> 455223 |
| 50 | 3000 | 4450 | OPAL | grey | 53/40/1140 | IP20 | yes | surface | >> 319310 |
| 50 | 3000 | 4450 | OPAL | white | 53/40/1140 | IP20 | yes | surface | >> 319358 |
| 50 | 3000 | 4450 | OPAL | black | 53/40/1140 | IP20 | yes | surface | >> 319396 |
| 50 | 3000 | 4450 | OPAL | grey | 53/40/1140 | IP20 | | surface | >> 318139 |
| 50 | 3000 | 4450 | OPAL | white | 53/40/1140 | IP20 | | surface | >> 318153 |
| 50 | 3000 | 4450 | OPAL | black | 53/40/1140 | IP20 | | surface | >> 318177 |
| 50 | 4000 | 4800 | OPAL | grey | 53/40/1140 | IP20 | yes | surface | >> 319303 |
| 50 | 4000 | 4800 | OPAL | white | 53/40/1140 | IP20 | yes | surface | >> 319341 |
| 50 | 4000 | 4800 | OPAL | black | 53/40/1140 | IP20 | yes | surface | >> 319389 |
| 50 | 4000 | 4800 | OPAL | grey | 53/40/1140 | IP20 | | surface | >> 318122 |
| 50 | 4000 | 4800 | OPAL | white | 53/40/1140 | IP20 | | surface | >> 318146 |
| 50 | 4000 | 4800 | OPAL | black | 53/40/1140 | IP20 | | surface | >> 318160 |
| 50 | 3000 | 5500 | PRM | grey | 53/40/1140 | IP20 | yes | surface | >> 454639 |
| 50 | 3000 | 5500 | PRM | white | 53/40/1140 | IP20 | yes | surface | >> 454677 |
| 50 | 3000 | 5500 | PRM | black | 53/40/1140 | IP20 | yes | surface | >> 454714 |
| 50 | 3000 | 5500 | PRM | grey | 53/40/1140 | IP20 | | surface | >> 454615 |
| 50 | 3000 | 5500 | PRM | white | 53/40/1140 | IP20 | | surface | >> 454653 |
| 50 | 3000 | 5500 | PRM | black | 53/40/1140 | IP20 | | surface | >> 454691 |
| 50 | 4000 | 5900 | PRM | grey | 53/40/1140 | IP20 | yes | surface | >> 454622 |
| 50 | 4000 | 5900 | PRM | white | 53/40/1140 | IP20 | yes | surface | >> 454660 |
| 50 | 4000 | 5900 | PRM | black | 53/40/1140 | IP20 | yes | surface | >> 454707 |
| 50 | 4000 | 5900 | PRM | grey | 53/40/1140 | IP20 | | surface | >> 454608 |
| 50 | 4000 | 5900 | PRM | white | 53/40/1140 | IP20 | | surface | >> 454646 |
| 50 | 4000 | 5900 | PRM | black | 53/40/1140 | IP20 | | surface | >> 454684 |

BARIS 40 LED suspended

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Colour of the body | Dimensions (H/W/T/S) [mm] | Ingress protection | DIMM DALI | Mounting version | Index |
|-----------------------------------|------------------------|---------------------|---------------|--------------------|---------------------------|--------------------|-----------|------------------|---------------------------------|
| 14 | 3000 | 1300 | OPAL | grey | 53/40/860 | IP20 | yes | suspended | >> 930812 |
| 14 | 3000 | 1450 | PRM | white | 53/40/860 | IP20 | yes | suspended | >> 931147 |

BARIS 40 LED

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Colour of the body | Dimensions (H/W/T/S) [mm] | Ingress protection | DIMM DALI | Mounting version | Index |
|-----------------------------------|------------------------|---------------------|---------------|--------------------|---------------------------|--------------------|-----------|------------------|---------------------------------|
| 14 | 3000 | 1300 | OPAL | black | 53/40/860 | IP20 | yes | suspended | >> 931154 |
| 14 | 3000 | 1300 | OPAL | grey | 53/40/860 | IP20 | | suspended | >> 930874 |
| 14 | 3000 | 1450 | PRM | white | 53/40/860 | IP20 | yes | suspended | >> 930881 |
| 14 | 3000 | 1300 | OPAL | black | 53/40/860 | IP20 | | suspended | >> 930898 |
| 14 | 4000 | 1400 | OPAL | grey | 53/40/860 | IP20 | yes | suspended | >> 925351 |
| 14 | 4000 | 1400 | OPAL | white | 53/40/860 | IP20 | yes | suspended | >> 930386 |
| 14 | 4000 | 1400 | OPAL | black | 53/40/860 | IP20 | yes | suspended | >> 930393 |
| 14 | 4000 | 1400 | OPAL | grey | 53/40/860 | IP20 | | suspended | >> 925467 |
| 14 | 4000 | 1400 | OPAL | white | 53/40/860 | IP20 | | suspended | >> 925474 |
| 14 | 4000 | 1400 | OPAL | black | 53/40/860 | IP20 | | suspended | >> 925481 |
| 14 | 3000 | 1450 | PRM | grey | 53/40/860 | IP20 | yes | suspended | >> 930836 |
| 14 | 3000 | 1300 | OPAL | white | 53/40/860 | IP20 | yes | suspended | >> 931161 |
| 14 | 3000 | 1450 | PRM | black | 53/40/860 | IP20 | yes | suspended | >> 931178 |
| 14 | 3000 | 1450 | PRM | grey | 53/40/860 | IP20 | | suspended | >> 930935 |
| 14 | 3000 | 1300 | OPAL | white | 53/40/860 | IP20 | | suspended | >> 930942 |
| 14 | 3000 | 1450 | PRM | black | 53/40/860 | IP20 | | suspended | >> 930959 |
| 14 | 4000 | 1550 | PRM | grey | 53/40/860 | IP20 | yes | suspended | >> 925382 |
| 14 | 4000 | 1550 | PRM | white | 53/40/860 | IP20 | yes | suspended | >> 930409 |
| 14 | 4000 | 1550 | PRM | black | 53/40/860 | IP20 | yes | suspended | >> 930416 |
| 14 | 4000 | 1550 | PRM | grey | 53/40/860 | IP20 | | suspended | >> 925559 |
| 14 | 4000 | 1550 | PRM | white | 53/40/860 | IP20 | | suspended | >> 925566 |
| 14 | 4000 | 1550 | PRM | black | 53/40/860 | IP20 | | suspended | >> 925573 |
| 14 | 3000 | 1300 | OPAL | grey | 53/40/860 | IP44 | yes | suspended | >> 930805 |
| 14 | 3000 | 1300 | OPAL | white | 53/40/860 | IP44 | yes | suspended | >> 931260 |
| 14 | 3000 | 1300 | OPAL | black | 53/40/860 | IP44 | yes | suspended | >> 931277 |
| 14 | 3000 | 1300 | OPAL | grey | 53/40/860 | IP44 | | suspended | >> 930843 |
| 14 | 3000 | 1300 | OPAL | white | 53/40/860 | IP44 | | suspended | >> 930850 |
| 14 | 3000 | 1300 | OPAL | black | 53/40/860 | IP44 | | suspended | >> 930867 |
| 14 | 4000 | 1400 | OPAL | grey | 53/40/860 | IP44 | yes | suspended | >> 925344 |
| 14 | 4000 | 1400 | OPAL | white | 53/40/860 | IP44 | yes | suspended | >> 930508 |
| 14 | 4000 | 1400 | OPAL | black | 53/40/860 | IP44 | yes | suspended | >> 930515 |
| 14 | 4000 | 1400 | OPAL | grey | 53/40/860 | IP44 | | suspended | >> 925429 |
| 14 | 4000 | 1400 | OPAL | white | 53/40/860 | IP44 | | suspended | >> 925436 |
| 14 | 4000 | 1400 | OPAL | black | 53/40/860 | IP44 | | suspended | >> 925443 |
| 14 | 3000 | 1450 | PRM | grey | 53/40/860 | IP44 | yes | suspended | >> 930829 |
| 14 | 3000 | 1450 | PRM | white | 53/40/860 | IP44 | yes | suspended | >> 931284 |
| 14 | 3000 | 1450 | PRM | black | 53/40/860 | IP44 | yes | suspended | >> 931291 |
| 14 | 3000 | 1450 | PRM | grey | 53/40/860 | IP44 | | suspended | >> 930904 |

BARIS 40 LED

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Colour of the body | Dimensions (H/W/T/S) [mm] | Ingress protection | DIMM DALI | Mounting version | Index |
|-----------------------------------|------------------------|---------------------|---------------|--------------------|---------------------------|--------------------|-----------|------------------|---------------------------------|
| 14 | 3000 | 1450 | PRM | white | 53/40/860 | IP44 | | suspended | >> 930911 |
| 14 | 3000 | 1450 | PRM | black | 53/40/860 | IP44 | | suspended | >> 930928 |
| 14 | 4000 | 1550 | PRM | grey | 53/40/860 | IP44 | yes | suspended | >> 925375 |
| 14 | 4000 | 1550 | PRM | white | 53/40/860 | IP44 | yes | suspended | >> 930522 |
| 14 | 4000 | 1550 | PRM | black | 53/40/860 | IP44 | yes | suspended | >> 930539 |
| 14 | 4000 | 1550 | PRM | grey | 53/40/860 | IP44 | | suspended | >> 925528 |
| 14 | 4000 | 1550 | PRM | white | 53/40/860 | IP44 | | suspended | >> 925535 |
| 14 | 4000 | 1550 | PRM | black | 53/40/860 | IP44 | | suspended | >> 925542 |
| 18 | 3000 | 1700 | OPAL | grey | 53/40/1140 | IP20 | | suspended | >> 318573 |
| 18 | 3000 | 1700 | OPAL | white | 53/40/1140 | IP20 | | suspended | >> 318610 |
| 18 | 3000 | 1700 | OPAL | black | 53/40/1140 | IP20 | | suspended | >> 318658 |
| 18 | 4000 | 1850 | OPAL | grey | 53/40/1140 | IP20 | | suspended | >> 318566 |
| 18 | 4000 | 1850 | OPAL | white | 53/40/1140 | IP20 | | suspended | >> 318603 |
| 18 | 4000 | 1850 | OPAL | black | 53/40/1140 | IP20 | | suspended | >> 318641 |
| 18 | 3000 | 2100 | PRM | grey | 53/40/1140 | IP20 | | suspended | >> 454011 |
| 18 | 3000 | 2100 | PRM | white | 53/40/1140 | IP20 | | suspended | >> 454035 |
| 18 | 3000 | 2100 | PRM | black | 53/40/1140 | IP20 | | suspended | >> 454059 |
| 18 | 4000 | 2300 | PRM | grey | 53/40/1140 | IP20 | | suspended | >> 454004 |
| 18 | 4000 | 2300 | PRM | white | 53/40/1140 | IP20 | | suspended | >> 454028 |
| 18 | 4000 | 2300 | PRM | black | 53/40/1140 | IP20 | | suspended | >> 454042 |
| 18 | 3000 | 1700 | OPAL | grey | 53/40/1140 | IP44 | | suspended | >> 319471 |
| 18 | 3000 | 1700 | OPAL | white | 53/40/1140 | IP44 | | suspended | >> 319518 |
| 18 | 3000 | 1700 | OPAL | black | 53/40/1140 | IP44 | | suspended | >> 319556 |
| 18 | 4000 | 1850 | OPAL | grey | 53/40/1140 | IP44 | | suspended | >> 319464 |
| 18 | 4000 | 1850 | OPAL | white | 53/40/1140 | IP44 | | suspended | >> 319501 |
| 18 | 4000 | 1850 | OPAL | black | 53/40/1140 | IP44 | | suspended | >> 319549 |
| 18 | 3000 | 2100 | PRM | grey | 53/40/1140 | IP44 | | suspended | >> 454073 |
| 18 | 3000 | 2100 | PRM | white | 53/40/1140 | IP44 | | suspended | >> 454097 |
| 18 | 3000 | 2100 | PRM | black | 53/40/1140 | IP44 | | suspended | >> 454110 |
| 18 | 4000 | 2300 | PRM | grey | 53/40/1140 | IP44 | | suspended | >> 454066 |
| 18 | 4000 | 2300 | PRM | white | 53/40/1140 | IP44 | | suspended | >> 454080 |
| 18 | 4000 | 2300 | PRM | black | 53/40/1140 | IP44 | | suspended | >> 454103 |
| 23 | 3000 | 2100 | OPAL | grey | 53/40/860 | IP20 | yes | suspended | >> 931024 |
| 23 | 3000 | 2100 | OPAL | white | 53/40/860 | IP20 | yes | suspended | >> 931109 |
| 23 | 3000 | 2100 | OPAL | black | 53/40/860 | IP20 | yes | suspended | >> 931116 |
| 23 | 3000 | 2100 | OPAL | grey | 53/40/860 | IP20 | | suspended | >> 930683 |
| 23 | 3000 | 2100 | OPAL | white | 53/40/860 | IP20 | | suspended | >> 930690 |
| 23 | 3000 | 2100 | OPAL | black | 53/40/860 | IP20 | | suspended | >> 930706 |

BARIS 40 LED

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Colour of the body | Dimensions (H/W/T/S) [mm] | Ingress protection | DIMM DALI | Mounting version | Index |
|-----------------------------------|------------------------|---------------------|---------------|--------------------|---------------------------|--------------------|-----------|------------------|---------------------------------|
| 23 | 4000 | 2300 | OPAL | grey | 53/40/860 | IP20 | yes | suspended | >> 925658 |
| 23 | 4000 | 2300 | OPAL | white | 53/40/860 | IP20 | yes | suspended | >> 930348 |
| 23 | 4000 | 2300 | OPAL | black | 53/40/860 | IP20 | yes | suspended | >> 930355 |
| 23 | 4000 | 2300 | OPAL | grey | 53/40/860 | IP20 | | suspended | >> 925177 |
| 23 | 4000 | 2300 | OPAL | white | 53/40/860 | IP20 | | suspended | >> 925184 |
| 23 | 4000 | 2300 | OPAL | black | 53/40/860 | IP20 | | suspended | >> 925191 |
| 23 | 3000 | 2350 | PRM | grey | 53/40/860 | IP20 | yes | suspended | >> 931048 |
| 23 | 3000 | 2350 | PRM | white | 53/40/860 | IP20 | yes | suspended | >> 931123 |
| 23 | 3000 | 2350 | PRM | black | 53/40/860 | IP20 | yes | suspended | >> 931130 |
| 23 | 3000 | 2350 | PRM | grey | 53/40/860 | IP20 | | suspended | >> 930744 |
| 23 | 3000 | 2350 | PRM | white | 53/40/860 | IP20 | | suspended | >> 930751 |
| 23 | 3000 | 2350 | PRM | black | 53/40/860 | IP20 | | suspended | >> 930768 |
| 23 | 4000 | 2500 | PRM | grey | 53/40/860 | IP20 | yes | suspended | >> 925689 |
| 23 | 4000 | 2500 | PRM | white | 53/40/860 | IP20 | yes | suspended | >> 930362 |
| 23 | 4000 | 2500 | PRM | black | 53/40/860 | IP20 | yes | suspended | >> 930379 |
| 23 | 4000 | 2500 | PRM | grey | 53/40/860 | IP20 | | suspended | >> 925276 |
| 23 | 4000 | 2500 | PRM | white | 53/40/860 | IP20 | | suspended | >> 925283 |
| 23 | 4000 | 2500 | PRM | black | 53/40/860 | IP20 | | suspended | >> 925290 |
| 23 | 3000 | 2100 | OPAL | grey | 53/40/860 | IP44 | yes | suspended | >> 931031 |
| 23 | 3000 | 2100 | OPAL | white | 53/40/860 | IP44 | yes | suspended | >> 931222 |
| 23 | 3000 | 2100 | OPAL | black | 53/40/860 | IP44 | yes | suspended | >> 931239 |
| 23 | 3000 | 2100 | OPAL | grey | 53/40/860 | IP44 | | suspended | >> 930713 |
| 23 | 3000 | 2100 | OPAL | white | 53/40/860 | IP44 | | suspended | >> 930720 |
| 23 | 3000 | 2100 | OPAL | black | 53/40/860 | IP44 | | suspended | >> 930737 |
| 23 | 4000 | 2300 | OPAL | grey | 53/40/860 | IP44 | yes | suspended | >> 925665 |
| 23 | 4000 | 2300 | OPAL | white | 53/40/860 | IP44 | yes | suspended | >> 930461 |
| 23 | 4000 | 2300 | OPAL | black | 53/40/860 | IP44 | yes | suspended | >> 930478 |
| 23 | 4000 | 2300 | OPAL | grey | 53/40/860 | IP44 | | suspended | >> 925207 |
| 23 | 4000 | 2300 | OPAL | white | 53/40/860 | IP44 | | suspended | >> 925214 |
| 23 | 4000 | 2300 | OPAL | black | 53/40/860 | IP44 | | suspended | >> 925221 |
| 23 | 3000 | 2350 | PRM | white | 53/40/860 | IP44 | yes | suspended | >> 931246 |
| 23 | 3000 | 2350 | PRM | black | 53/40/860 | IP44 | yes | suspended | >> 931253 |
| 23 | 3000 | 2350 | PRM | grey | 53/40/860 | IP44 | yes | suspended | >> 931055 |
| 23 | 3000 | 2350 | PRM | grey | 53/40/860 | IP44 | | suspended | >> 930799 |
| 23 | 3000 | 2350 | PRM | white | 53/40/860 | IP44 | | suspended | >> 930775 |
| 23 | 3000 | 2350 | PRM | black | 53/40/860 | IP44 | | suspended | >> 930782 |
| 23 | 4000 | 2500 | PRM | grey | 53/40/860 | IP44 | yes | suspended | >> 925696 |
| 23 | 4000 | 2500 | PRM | white | 53/40/860 | IP44 | yes | suspended | >> 930485 |

BARIS 40 LED

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Colour of the body | Dimensions (H/W/T/S) [mm] | Ingress protection | DIMM DALI | Mounting version | Index |
|-----------------------------------|------------------------|---------------------|---------------|--------------------|---------------------------|--------------------|-----------|------------------|---------------------------------|
| 23 | 4000 | 2500 | PRM | black | 53/40/860 | IP44 | yes | suspended | >> 930492 |
| 23 | 4000 | 2500 | PRM | grey | 53/40/860 | IP44 | | suspended | >> 925337 |
| 23 | 4000 | 2500 | PRM | white | 53/40/860 | IP44 | | suspended | >> 925313 |
| 23 | 4000 | 2500 | PRM | black | 53/40/860 | IP44 | | suspended | >> 925320 |
| 33 | 3000 | 2600 | OPAL | grey | 53/40/1140 | IP20 | | suspended | >> 319594 |
| 33 | 3000 | 2600 | OPAL | white | 53/40/1140 | IP20 | | suspended | >> 319617 |
| 33 | 3000 | 2600 | OPAL | black | 53/40/1140 | IP20 | | suspended | >> 319631 |
| 33 | 4000 | 2800 | OPAL | grey | 53/40/1140 | IP20 | | suspended | >> 319587 |
| 33 | 4000 | 2800 | OPAL | white | 53/40/1140 | IP20 | | suspended | >> 319600 |
| 33 | 4000 | 2800 | OPAL | black | 53/40/1140 | IP20 | | suspended | >> 319624 |
| 33 | 3000 | 3200 | PRM | grey | 53/40/1140 | IP20 | | suspended | >> 454196 |
| 33 | 3000 | 3200 | PRM | white | 53/40/1140 | IP20 | | suspended | >> 454219 |
| 33 | 3000 | 3200 | PRM | black | 53/40/1140 | IP20 | | suspended | >> 454233 |
| 33 | 4000 | 3450 | PRM | grey | 53/40/1140 | IP20 | | suspended | >> 454189 |
| 33 | 4000 | 3450 | PRM | white | 53/40/1140 | IP20 | | suspended | >> 454202 |
| 33 | 4000 | 3450 | PRM | black | 53/40/1140 | IP20 | | suspended | >> 454226 |
| 33 | 3000 | 2600 | OPAL | grey | 53/40/1140 | IP44 | | suspended | >> 318320 |
| 33 | 3000 | 2600 | OPAL | white | 53/40/1140 | IP44 | | suspended | >> 318344 |
| 33 | 3000 | 2600 | OPAL | black | 53/40/1140 | IP44 | | suspended | >> 318368 |
| 33 | 4000 | 2800 | OPAL | grey | 53/40/1140 | IP44 | | suspended | >> 318313 |
| 33 | 4000 | 2800 | OPAL | white | 53/40/1140 | IP44 | | suspended | >> 318337 |
| 33 | 4000 | 2800 | OPAL | black | 53/40/1140 | IP44 | | suspended | >> 318351 |
| 33 | 3000 | 3200 | PRM | grey | 53/40/1140 | IP44 | | suspended | >> 454257 |
| 33 | 3000 | 3200 | PRM | white | 53/40/1140 | IP44 | | suspended | >> 454271 |
| 33 | 3000 | 3200 | PRM | black | 53/40/1140 | IP44 | | suspended | >> 454295 |
| 33 | 4000 | 3450 | PRM | grey | 53/40/1140 | IP44 | | suspended | >> 454240 |
| 33 | 4000 | 3450 | PRM | white | 53/40/1140 | IP44 | | suspended | >> 454264 |
| 33 | 4000 | 3450 | PRM | black | 53/40/1140 | IP44 | | suspended | >> 454288 |
| 39 | 3000 | 3400 | OPAL | grey | 53/40/1421 | IP20 | | suspended | >> 318757 |
| 39 | 3000 | 3400 | OPAL | white | 53/40/1421 | IP20 | | suspended | >> 318795 |
| 39 | 3000 | 3400 | OPAL | black | 53/40/1421 | IP20 | | suspended | >> 318832 |
| 39 | 4000 | 3700 | OPAL | grey | 53/40/1421 | IP20 | | suspended | >> 318740 |
| 39 | 4000 | 3700 | OPAL | white | 53/40/1421 | IP20 | | suspended | >> 318788 |
| 39 | 4000 | 3700 | OPAL | black | 53/40/1421 | IP20 | | suspended | >> 318825 |
| 39 | 3000 | 4200 | PRM | grey | 53/40/1421 | IP20 | | suspended | >> 454738 |
| 39 | 3000 | 4200 | PRM | white | 53/40/1421 | IP20 | | suspended | >> 454752 |
| 39 | 3000 | 4200 | PRM | black | 53/40/1421 | IP20 | | suspended | >> 454776 |
| 39 | 4000 | 4550 | PRM | grey | 53/40/1421 | IP20 | | suspended | >> 454721 |

BARIS 40 LED

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Colour of the body | Dimensions (H/W/T/S) [mm] | Ingress protection | DIMM DALI | Mounting version | Index |
|-----------------------------------|------------------------|---------------------|---------------|--------------------|---------------------------|--------------------|-----------|------------------|---------------------------------|
| 39 | 4000 | 4550 | PRM | white | 53/40/1421 | IP20 | | suspended | >> 454745 |
| 39 | 4000 | 4550 | PRM | black | 53/40/1421 | IP20 | | suspended | >> 454769 |
| 39 | 3000 | 3600 | OPAL | grey | 53/40/860 | IP20 | yes | suspended | >> 930669 |
| 39 | 3000 | 3600 | OPAL | white | 53/40/860 | IP20 | yes | suspended | >> 931062 |
| 39 | 3000 | 3600 | OPAL | black | 53/40/860 | IP20 | yes | suspended | >> 931079 |
| 39 | 3000 | 3600 | OPAL | grey | 53/40/860 | IP20 | | suspended | >> 930546 |
| 39 | 3000 | 3600 | OPAL | white | 53/40/860 | IP20 | | suspended | >> 930553 |
| 39 | 3000 | 3600 | OPAL | black | 53/40/860 | IP20 | | suspended | >> 930560 |
| 39 | 4000 | 3900 | OPAL | grey | 53/40/860 | IP20 | yes | suspended | >> 925108 |
| 39 | 4000 | 3900 | OPAL | white | 53/40/860 | IP20 | yes | suspended | >> 930300 |
| 39 | 4000 | 3900 | OPAL | black | 53/40/860 | IP20 | yes | suspended | >> 930317 |
| 39 | 4000 | 3900 | OPAL | grey | 53/40/860 | IP20 | | suspended | >> 466830 |
| 39 | 4000 | 3900 | OPAL | white | 53/40/860 | IP20 | | suspended | >> 466847 |
| 39 | 4000 | 3900 | OPAL | black | 53/40/860 | IP20 | | suspended | >> 466854 |
| 39 | 3000 | 4150 | PRM | grey | 53/40/860 | IP20 | yes | suspended | >> 931000 |
| 39 | 3000 | 4150 | PRM | white | 53/40/860 | IP20 | yes | suspended | >> 931086 |
| 39 | 3000 | 4150 | PRM | black | 53/40/860 | IP20 | yes | suspended | >> 931093 |
| 39 | 3000 | 4150 | PRM | grey | 53/40/860 | IP20 | | suspended | >> 930607 |
| 39 | 3000 | 4150 | PRM | white | 53/40/860 | IP20 | | suspended | >> 930614 |
| 39 | 3000 | 4150 | PRM | black | 53/40/860 | IP20 | | suspended | >> 930621 |
| 39 | 4000 | 4450 | PRM | grey | 53/40/860 | IP20 | yes | suspended | >> 925627 |
| 39 | 4000 | 4450 | PRM | white | 53/40/860 | IP20 | yes | suspended | >> 930324 |
| 39 | 4000 | 4450 | PRM | black | 53/40/860 | IP20 | yes | suspended | >> 930331 |
| 39 | 4000 | 4450 | PRM | grey | 53/40/860 | IP20 | | suspended | >> 925030 |
| 39 | 4000 | 4450 | PRM | white | 53/40/860 | IP20 | | suspended | >> 925047 |
| 39 | 4000 | 4450 | PRM | black | 53/40/860 | IP20 | | suspended | >> 925054 |
| 39 | 3000 | 3400 | OPAL | grey | 53/40/1421 | IP44 | | suspended | >> 319839 |
| 39 | 3000 | 3400 | OPAL | white | 53/40/1421 | IP44 | | suspended | >> 319877 |
| 39 | 3000 | 3400 | OPAL | black | 53/40/1421 | IP44 | | suspended | >> 319914 |
| 39 | 4000 | 3700 | OPAL | grey | 53/40/1421 | IP44 | | suspended | >> 319822 |
| 39 | 4000 | 3700 | OPAL | white | 53/40/1421 | IP44 | | suspended | >> 319860 |
| 39 | 4000 | 3700 | OPAL | black | 53/40/1421 | IP44 | | suspended | >> 319907 |
| 39 | 3000 | 4200 | PRM | grey | 53/40/1421 | IP44 | | suspended | >> 454790 |
| 39 | 3000 | 4200 | PRM | white | 53/40/1421 | IP44 | | suspended | >> 454813 |
| 39 | 3000 | 4200 | PRM | black | 53/40/1421 | IP44 | | suspended | >> 454837 |
| 39 | 4000 | 4550 | PRM | grey | 53/40/1421 | IP44 | | suspended | >> 454783 |
| 39 | 4000 | 4550 | PRM | white | 53/40/1421 | IP44 | | suspended | >> 454806 |
| 39 | 4000 | 4550 | PRM | black | 53/40/1421 | IP44 | | suspended | >> 454820 |

BARIS 40 LED

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Colour of the body | Dimensions (H/W/T/S) [mm] | Ingress protection | DIMM DALI | Mounting version | Index |
|-----------------------------------|------------------------|---------------------|---------------|--------------------|---------------------------|--------------------|-----------|------------------|---------------------------------|
| 39 | 3000 | 3600 | OPAL | grey | 53/40/860 | IP44 | yes | suspended | >> 930676 |
| 39 | 3000 | 3600 | OPAL | white | 53/40/860 | IP44 | yes | suspended | >> 931185 |
| 39 | 3000 | 3600 | OPAL | black | 53/40/860 | IP44 | yes | suspended | >> 931192 |
| 39 | 3000 | 3600 | OPAL | grey | 53/40/860 | IP44 | | suspended | >> 930577 |
| 39 | 3000 | 3600 | OPAL | white | 53/40/860 | IP44 | | suspended | >> 930584 |
| 39 | 3000 | 3600 | OPAL | black | 53/40/860 | IP44 | | suspended | >> 930591 |
| 39 | 4000 | 3900 | OPAL | grey | 53/40/860 | IP44 | yes | suspended | >> 925115 |
| 39 | 4000 | 3900 | OPAL | white | 53/40/860 | IP44 | yes | suspended | >> 930423 |
| 39 | 4000 | 3900 | OPAL | black | 53/40/860 | IP44 | yes | suspended | >> 930430 |
| 39 | 4000 | 3900 | OPAL | grey | 53/40/860 | IP44 | | suspended | >> 466861 |
| 39 | 4000 | 3900 | OPAL | white | 53/40/860 | IP44 | | suspended | >> 466878 |
| 39 | 4000 | 3900 | OPAL | black | 53/40/860 | IP44 | | suspended | >> 466885 |
| 39 | 3000 | 4150 | PRM | grey | 53/40/860 | IP44 | yes | suspended | >> 931017 |
| 39 | 3000 | 4150 | PRM | white | 53/40/860 | IP44 | yes | suspended | >> 931208 |
| 39 | 3000 | 4150 | PRM | black | 53/40/860 | IP44 | yes | suspended | >> 931215 |
| 39 | 3000 | 4150 | PRM | grey | 53/40/860 | IP44 | | suspended | >> 930638 |
| 39 | 3000 | 4150 | PRM | white | 53/40/860 | IP44 | | suspended | >> 930645 |
| 39 | 3000 | 4150 | PRM | black | 53/40/860 | IP44 | | suspended | >> 930652 |
| 39 | 4000 | 4450 | PRM | grey | 53/40/860 | IP44 | yes | suspended | >> 925634 |
| 39 | 4000 | 4450 | PRM | white | 53/40/860 | IP44 | yes | suspended | >> 930447 |
| 39 | 4000 | 4450 | PRM | black | 53/40/860 | IP44 | yes | suspended | >> 930454 |
| 39 | 4000 | 4450 | PRM | grey | 53/40/860 | IP44 | | suspended | >> 925061 |
| 39 | 4000 | 4450 | PRM | white | 53/40/860 | IP44 | | suspended | >> 925078 |
| 39 | 4000 | 4450 | PRM | black | 53/40/860 | IP44 | | suspended | >> 925085 |
| 46 | 3000 | 3900 | OPAL | grey | 53/40/1421 | IP20 | yes | suspended | >> 318771 |
| 46 | 3000 | 3900 | OPAL | white | 53/40/1421 | IP20 | yes | suspended | >> 318818 |
| 46 | 3000 | 3900 | OPAL | black | 53/40/1421 | IP20 | yes | suspended | >> 318856 |
| 46 | 3000 | 3900 | OPAL | grey | 53/40/1421 | IP20 | | suspended | >> 319952 |
| 46 | 3000 | 3900 | OPAL | white | 53/40/1421 | IP20 | | suspended | >> 319976 |
| 46 | 3000 | 3900 | OPAL | black | 53/40/1421 | IP20 | | suspended | >> 319990 |
| 46 | 4000 | 4300 | OPAL | grey | 53/40/1421 | IP20 | yes | suspended | >> 318764 |
| 46 | 4000 | 4300 | OPAL | white | 53/40/1421 | IP20 | yes | suspended | >> 318801 |
| 46 | 4000 | 4300 | OPAL | black | 53/40/1421 | IP20 | yes | suspended | >> 318849 |
| 46 | 4000 | 4300 | OPAL | grey | 53/40/1421 | IP20 | | suspended | >> 319945 |
| 46 | 4000 | 4300 | OPAL | white | 53/40/1421 | IP20 | | suspended | >> 319969 |
| 46 | 4000 | 4300 | OPAL | black | 53/40/1421 | IP20 | | suspended | >> 319983 |
| 46 | 3000 | 4800 | PRM | grey | 53/40/1421 | IP20 | yes | suspended | >> 454936 |
| 46 | 3000 | 4800 | PRM | white | 53/40/1421 | IP20 | yes | suspended | >> 454974 |

BARIS 40 LED

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Colour of the body | Dimensions (H/W/T/S) [mm] | Ingress protection | DIMM DALI | Mounting version | Index |
|-----------------------------------|------------------------|---------------------|---------------|--------------------|---------------------------|--------------------|-----------|------------------|---------------------------------|
| 46 | 3000 | 4800 | PRM | black | 53/40/1421 | IP20 | yes | suspended | >> 455018 |
| 46 | 3000 | 4800 | PRM | grey | 53/40/1421 | IP20 | | suspended | >> 454912 |
| 46 | 3000 | 4800 | PRM | white | 53/40/1421 | IP20 | | suspended | >> 454950 |
| 46 | 3000 | 4800 | PRM | black | 53/40/1421 | IP20 | | suspended | >> 454998 |
| 46 | 4000 | 5300 | PRM | grey | 53/40/1421 | IP20 | yes | suspended | >> 454929 |
| 46 | 4000 | 5300 | PRM | white | 53/40/1421 | IP20 | yes | suspended | >> 454967 |
| 46 | 4000 | 5300 | PRM | black | 53/40/1421 | IP20 | yes | suspended | >> 455001 |
| 46 | 4000 | 5300 | PRM | grey | 53/40/1421 | IP20 | | suspended | >> 454905 |
| 46 | 4000 | 5300 | PRM | white | 53/40/1421 | IP20 | | suspended | >> 454943 |
| 46 | 4000 | 5300 | PRM | black | 53/40/1421 | IP20 | | suspended | >> 454981 |
| 46 | 3000 | 3900 | OPAL | grey | 53/40/1421 | IP44 | yes | suspended | >> 319853 |
| 46 | 3000 | 3900 | OPAL | white | 53/40/1421 | IP44 | yes | suspended | >> 319891 |
| 46 | 3000 | 3900 | OPAL | black | 53/40/1421 | IP44 | yes | suspended | >> 319938 |
| 46 | 3000 | 3900 | OPAL | grey | 53/40/1421 | IP44 | | suspended | >> 318504 |
| 46 | 3000 | 3900 | OPAL | white | 53/40/1421 | IP44 | | suspended | >> 318528 |
| 46 | 3000 | 3900 | OPAL | black | 53/40/1421 | IP44 | | suspended | >> 318542 |
| 46 | 4000 | 4300 | OPAL | grey | 53/40/1421 | IP44 | yes | suspended | >> 319846 |
| 46 | 4000 | 4300 | OPAL | white | 53/40/1421 | IP44 | yes | suspended | >> 319884 |
| 46 | 4000 | 4300 | OPAL | black | 53/40/1421 | IP44 | yes | suspended | >> 319921 |
| 46 | 4000 | 4300 | OPAL | grey | 53/40/1421 | IP44 | | suspended | >> 318498 |
| 46 | 4000 | 4300 | OPAL | white | 53/40/1421 | IP44 | | suspended | >> 318511 |
| 46 | 4000 | 4300 | OPAL | black | 53/40/1421 | IP44 | | suspended | >> 318535 |
| 46 | 3000 | 4800 | PRM | grey | 53/40/1421 | IP44 | yes | suspended | >> 455056 |
| 46 | 3000 | 4800 | PRM | white | 53/40/1421 | IP44 | yes | suspended | >> 455094 |
| 46 | 3000 | 4800 | PRM | black | 53/40/1421 | IP44 | yes | suspended | >> 455131 |
| 46 | 3000 | 4800 | PRM | grey | 53/40/1421 | IP44 | | suspended | >> 455032 |
| 46 | 3000 | 4800 | PRM | white | 53/40/1421 | IP44 | | suspended | >> 455070 |
| 46 | 3000 | 4800 | PRM | black | 53/40/1421 | IP44 | | suspended | >> 455117 |
| 46 | 4000 | 5300 | PRM | grey | 53/40/1421 | IP44 | yes | suspended | >> 455049 |
| 46 | 4000 | 5300 | PRM | white | 53/40/1421 | IP44 | yes | suspended | >> 455087 |
| 46 | 4000 | 5300 | PRM | black | 53/40/1421 | IP44 | yes | suspended | >> 455124 |
| 46 | 4000 | 5300 | PRM | grey | 53/40/1421 | IP44 | | suspended | >> 455025 |
| 46 | 4000 | 5300 | PRM | white | 53/40/1421 | IP44 | | suspended | >> 455063 |
| 46 | 4000 | 5300 | PRM | black | 53/40/1421 | IP44 | | suspended | >> 455100 |
| 50 | 3000 | 4450 | OPAL | grey | 53/40/1140 | IP20 | yes | suspended | >> 318597 |
| 50 | 3000 | 4450 | OPAL | white | 53/40/1140 | IP20 | yes | suspended | >> 318634 |
| 50 | 3000 | 4450 | OPAL | black | 53/40/1140 | IP20 | yes | suspended | >> 318672 |
| 50 | 3000 | 4450 | OPAL | grey | 53/40/1140 | IP20 | | suspended | >> 318269 |

BARIS 40 LED

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Colour of the body | Dimensions (H/W/T/S) [mm] | Ingress protection | DIMM DALI | Mounting version | Index |
|-----------------------------------|------------------------|---------------------|---------------|--------------------|---------------------------|--------------------|-----------|------------------|---------------------------------|
| 50 | 3000 | 4450 | OPAL | white | 53/40/1140 | IP20 | | suspended | >> 318283 |
| 50 | 3000 | 4450 | OPAL | black | 53/40/1140 | IP20 | | suspended | >> 318306 |
| 50 | 4000 | 4800 | OPAL | grey | 53/40/1140 | IP20 | yes | suspended | >> 318580 |
| 50 | 4000 | 4800 | OPAL | white | 53/40/1140 | IP20 | yes | suspended | >> 318627 |
| 50 | 4000 | 4800 | OPAL | black | 53/40/1140 | IP20 | yes | suspended | >> 318665 |
| 50 | 4000 | 4800 | OPAL | grey | 53/40/1140 | IP20 | | suspended | >> 318252 |
| 50 | 4000 | 4800 | OPAL | white | 53/40/1140 | IP20 | | suspended | >> 318276 |
| 50 | 4000 | 4800 | OPAL | black | 53/40/1140 | IP20 | | suspended | >> 318290 |
| 50 | 3000 | 5500 | PRM | grey | 53/40/1140 | IP20 | yes | suspended | >> 454394 |
| 50 | 3000 | 5500 | PRM | white | 53/40/1140 | IP20 | yes | suspended | >> 454431 |
| 50 | 3000 | 5500 | PRM | black | 53/40/1140 | IP20 | yes | suspended | >> 454479 |
| 50 | 3000 | 5500 | PRM | grey | 53/40/1140 | IP20 | | suspended | >> 454370 |
| 50 | 3000 | 5500 | PRM | white | 53/40/1140 | IP20 | | suspended | >> 454417 |
| 50 | 3000 | 5500 | PRM | black | 53/40/1140 | IP20 | | suspended | >> 454455 |
| 50 | 4000 | 5900 | PRM | grey | 53/40/1140 | IP20 | yes | suspended | >> 454387 |
| 50 | 4000 | 5900 | PRM | white | 53/40/1140 | IP20 | yes | suspended | >> 454424 |
| 50 | 4000 | 5900 | PRM | black | 53/40/1140 | IP20 | yes | suspended | >> 454462 |
| 50 | 4000 | 5900 | PRM | grey | 53/40/1140 | IP20 | | suspended | >> 454363 |
| 50 | 4000 | 5900 | PRM | white | 53/40/1140 | IP20 | | suspended | >> 454400 |
| 50 | 4000 | 5900 | PRM | black | 53/40/1140 | IP20 | | suspended | >> 454448 |
| 50 | 3000 | 4450 | OPAL | grey | 53/40/1140 | IP44 | yes | suspended | >> 319495 |
| 50 | 3000 | 4450 | OPAL | white | 53/40/1140 | IP44 | yes | suspended | >> 319532 |
| 50 | 3000 | 4450 | OPAL | black | 53/40/1140 | IP44 | yes | suspended | >> 319570 |
| 50 | 3000 | 4450 | OPAL | grey | 53/40/1140 | IP44 | | suspended | >> 318191 |
| 50 | 3000 | 4450 | OPAL | white | 53/40/1140 | IP44 | | suspended | >> 318221 |
| 50 | 3000 | 4450 | OPAL | black | 53/40/1140 | IP44 | | suspended | >> 318245 |
| 50 | 4000 | 4800 | OPAL | grey | 53/40/1140 | IP44 | yes | suspended | >> 319488 |
| 50 | 4000 | 4800 | OPAL | white | 53/40/1140 | IP44 | yes | suspended | >> 319525 |
| 50 | 4000 | 4800 | OPAL | black | 53/40/1140 | IP44 | yes | suspended | >> 319563 |
| 50 | 4000 | 4800 | OPAL | grey | 53/40/1140 | IP44 | | suspended | >> 318184 |
| 50 | 4000 | 4800 | OPAL | white | 53/40/1140 | IP44 | | suspended | >> 318207 |
| 50 | 4000 | 4800 | OPAL | black | 53/40/1140 | IP44 | | suspended | >> 318238 |
| 50 | 3000 | 5500 | PRM | grey | 53/40/1140 | IP44 | yes | suspended | >> 454516 |
| 50 | 3000 | 5500 | PRM | white | 53/40/1140 | IP44 | yes | suspended | >> 454554 |
| 50 | 3000 | 5500 | PRM | black | 53/40/1140 | IP44 | yes | suspended | >> 454592 |
| 50 | 3000 | 5500 | PRM | grey | 53/40/1140 | IP44 | | suspended | >> 454493 |
| 50 | 3000 | 5500 | PRM | white | 53/40/1140 | IP44 | | suspended | >> 454530 |
| 50 | 3000 | 5500 | PRM | black | 53/40/1140 | IP44 | | suspended | >> 454578 |

BARIS 40 LED

GENERAL CARD

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Colour of the body | Dimensions (H/W/T/S) [mm] | Ingress protection | DIMM DALI | Mounting version | Index |
|-----------------------------------|------------------------|---------------------|---------------|--------------------|---------------------------|--------------------|-----------|------------------|---------------------------------|
| 50 | 4000 | 5900 | PRM | grey | 53/40/1140 | IP44 | yes | suspended | >> 454509 |
| 50 | 4000 | 5900 | PRM | white | 53/40/1140 | IP44 | yes | suspended | >> 454547 |
| 50 | 4000 | 5900 | PRM | black | 53/40/1140 | IP44 | yes | suspended | >> 454585 |
| 50 | 4000 | 5900 | PRM | grey | 53/40/1140 | IP44 | | suspended | >> 454486 |
| 50 | 4000 | 5900 | PRM | white | 53/40/1140 | IP44 | | suspended | >> 454523 |
| 50 | 4000 | 5900 | PRM | black | 53/40/1140 | IP44 | | suspended | >> 454561 |

Card creation date: 04 styczeń 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certyfikat CE - Nr.:/2022; 175/2020; 176/2020