

# FLATO LED M

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP54
<b>Impact resistance:</b>	IK08
<b>Rated power of the luminaire [W]*:</b>	17.00
<b>Luminous flux [lm]*:</b>	1750
<b>Supply voltage [V]:</b>	220-240
<b>Material of the body:</b>	PP
<b>Colour temperature [K]:</b>	4000; 5000
<b>Colour of the body:</b>	graphite
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	OPAL
<b>Beam angle [°]:</b>	120
<b>Dimensions (H/W/T/S) [mm]:</b>	132/185/74;
<b>Energy efficiency class:</b>	E

## CHARACTERISTICS

Compact LED floodlight ensuring even and stable directional lighting. The body, made of copolymer with rubber, increases its durability. The luminaire is equipped with anti-glare diffuser made of frosted PC with an UV stabiliser, which, despite the matt surface, transmits up to 80% of the light emitted by the diodes.

## APPLICATION

It can be used in general lighting applications: building façades, outbuildings, courtyards, in front of building entrances, billboards, advertisement boards and as a workplace luminaire for e.g. illuminating workplaces, workshops, construction sites. The smaller size and compact design make it more convenient to transport. The luminaire is designed for outdoor use, industrial applications or other applications where the lighting standards allow CRI <80.

# FLATO LED M

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Index
17	4000	1750	OPAL	132/185/74	<a href="#">&gt;&gt; 622021</a>
17	4000	1750	OPAL	132/185/74	<a href="#">&gt;&gt; 622427</a>
17	5000	1750	OPAL	132/185/74	<a href="#">&gt;&gt; 622076</a>

Card creation date: 28 March 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 186/2020; 186/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl