

# FLATO LED FL

## GENERAL CARD



### TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	45.00; 46.00
Colour temperature [K]:	4000
Luminous flux [lm]*:	3800
Ingress protection:	IP44
Impact resistance:	IK07
Color rendering index (Ra) >:	80
Electrical protection class:	II
Energy efficiency class:	F
Material of the body:	PP
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	OPAL
Beam angle [°]:	120
Mounting version:	surface, wall mounted
Working temperature [°C]:	from -20 to +35; from -40 to +35
Dimensions (H/W/T/S) [mm]:	285/261/64;

### CHARACTERISTICS

Compact LED floodlight ensuring even and stable directional lighting. The luminaire body, made of copolymer with rubber, increases its durability. The luminaire is equipped with anti-glare diffuser made of frosted PC with an UV stabiliser, which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. Also equipped with a comfortable mounting arm offering wide angle adjustment.

### APPLICATION

Compact floodlight providing even and stable directional lighting. It is used for general lighting: facades of buildings, farm buildings, yards, billboards, advertising boards, above gates and in front of building entrances.

# FLATO LED FL

## GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

FLATO LED FL surface, wall mounted

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	PIR	Dimensions (H/W/T/S) [mm]	Index
45	4000	3800	OPAL		285/261/64	<a href="#">&gt;&gt; 622182</a>
46	4000	3800	OPAL	yes	285/261/64	<a href="#">&gt;&gt; 622205</a>

Card creation date: 03 January 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 189/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)