RQ 160 LED PLUS N

GENERAL CARD

TECHNICAL PARAMETERS

Ingress protection:	IP33; IP44
Impact resistance:	IK08
Nominal power [W]:	17.00
Luminous flux [lm]*:	1700 - 2200
Colour temperature [K]:	3000; 4000
Color rendering index (Ra) >:	80
SDCM:	3
Electrical protection class:	II
Energy efficiency class:	D; E; F
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	OPAL; PRM; matt
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	166/86; 171/97;
PZH certificate:	B-BK-60112-0365/2022

CHARACTERISTICS

RQ 160 LED PLUS N is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent

APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.

RQ 160 LED PLUS N

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

Nominal power [W]	Luminous flux [lm]*	Colour temperature [K]	Diffuser type	Ingress protection	DIMM DALI	Emergency lighting [h]	Autotest	Dimensions (H/W/T/S) [mm]	Index
17	1700	3000	matt	IP33				166/86	>> 571770
17	1700	3000	matt	IP44	yes			171/97	>> 573989
17	1700	3000	matt	IP44				171/97	>> 573965
17	1700	3000	matt	IP44		3	yes	171/97	>> 574849
17	1700	3000	matt	IP33		3		166/86	>> 571787
17	1700	3000	matt	IP33	yes			166/86	>> 571794
17	1800	4000	matt	IP33	yes			166/86	>> 571701
17	1800	4000	matt	IP44	yes			171/97	>> 573996
17	1800	4000	matt	IP44				171/97	>> 573972
17	1800	4000	matt	IP44		3	yes	171/97	>> 574856
17	1800	4000	matt	IP33		3		166/86	>> 571695
17	1800	4000	matt	IP33				166/86	>> 571688
17	1900	3000	OPAL	IP44	yes			171/97	>> 574887
17	1900	3000	OPAL	IP44		3	yes	171/97	>> 574900
17	1900	3000	OPAL	IP44				171/97	>> 574863
17	1900	3000	OPAL	IP33				166/86	>> 571831
17	1900	3000	OPAL	IP33		3		166/86	>> 571848
17	1900	3000	OPAL	IP33	yes			166/86	>> 571855
17	2050	4000	OPAL	IP33				166/86	>> 571749
17	2050	4000	OPAL	IP44				171/97	>> 574870
17	2050	4000	OPAL	IP33		3		166/86	>> 571756
17	2050	4000	OPAL	IP44		3	yes	171/97	>> 574917
17	2050	4000	OPAL	IP44	yes			171/97	>> 574894
17	2050	4000	OPAL	IP33	yes			166/86	>> 571763
17	2100	3000	PRM	IP33		3		166/86	>> 571817
17	2100	3000	PRM	IP44		3	yes	171/97	>> 574962
17	2100	3000	PRM	IP44				171/97	>> 574924
17	2100	3000	PRM	IP44	yes			171/97	>> 574948
17	2100	3000	PRM	IP33	yes			166/86	>> 571824
17	2100	3000	PRM	IP33				166/86	>> 571800
17	2200	4000	PRM	IP33	yes			166/86	>> 571732
17	2200	4000	PRM	IP33				166/86	>> 571718
17	2200	4000	PRM	IP33		3		166/86	>> 571725
17	2200	4000	PRM	IP44		3	yes	171/97	>> 574979
17	2200	4000	PRM	IP44				171/97	>> 574931

RQ 160 LED PLUS N

GENERAL CARD

17	2200	4000	PRM	IP44	yes			171/97	>> 574955

RQ 160 LED PLUS N

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



RQ MAT



RQ Opal



RQ PRM

RQ 160 LED PLUS N

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
573637	Suspension RQ160 fi100 white ON/OFF. DALI

Card creation date: 26 August 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 210/2020; 28/2025; 321/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl