RQ 160 LED PLUS P

GENERAL CARD

TECHNICAL PARAMETERS

Ingress protection:	IP44/20
Impact resistance:	IK08
Rated power of the luminaire [W]*:	19.00; 22.00
Luminous flux [lm]*:	1700 - 2900
Colour temperature [K]:	3000; 4000
Color rendering index (Ra) >:	80
SDCM:	3
Electrical protection class:	II
Energy efficiency class:	D; E; F
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	OPAL; PRM; matt
Mounting version:	recessed
Dimensions (H/W/T/S) [mm]:	162/70;
PZH certificate:	B-BK-60112-0365/2022

CHARACTERISTICS

RQ 160 LED PLUS P is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Recessed-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.

RQ 160 LED PLUS P

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

RQ 160 LED PLUS P 19W

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser type	Beam angle [°]	Control	DIMM DALI	Index
19	1700	3000	matt	110	DALI	yes	>> 571527
19	1700	3000	matt	110			>> 571503
19	1800	4000	matt	110			>> 571329
19	1800	4000	matt	110	DALI	yes	>> 571343
19	1900	3000	OPAL	75			>> 571626
19	1900	3000	OPAL	75	DALI	yes	>> 571640
19	2050	4000	OPAL	75			>> 571442
19	2050	4000	OPAL	75	DALI	yes	>> 571466
19	2100	3000	PRM	115			>> 571565
19	2100	3000	PRM	115	DALI	yes	>> 571589
19	2200	4000	PRM	115			>> 571381
19	2200	4000	PRM	115	DALI	yes	>> 571404

RQ 160 LED PLUS P 22W

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser type	Beam angle [°]	Control	DIMM DALI	Index
22	2300	3000	matt	110			>> 571534
22	2300	3000	matt	110	DALI	yes	>> 571558
22	2450	4000	matt	110			>> 571350
22	2450	4000	matt	110	DALI	yes	>> 571374
22	2600	3000	OPAL	75			>> 571657
22	2600	3000	OPAL	75	DALI	yes	>> 571671
22	2750	4000	OPAL	75			>> 571473
22	2750	4000	OPAL	75	DALI	yes	>> 571497
22	2750	3000	PRM	115			>> 571596
22	2750	3000	PRM	115	DALI	yes	>> 571619
22	2900	4000	PRM	115			>> 571411
22	2900	4000	PRM	115	DALI	yes	>> 571435

RQ 160 LED PLUS P

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



RQ MAT



RQ Opal



RQ PRM

RQ 160 LED PLUS P

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
897269	Cover frame for RQ160 D205mm white RAL 9003



Cover frame for RQ160 D205mm white RAL 9003 (897269)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 211/2020; 322/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl