TYTAN 2 LED BASIC MULTI

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP66
Impact resistance:	IK09
Rated power [W] - range:	18-59
Luminous flux of the luminaire [lm] - range:	2700-8250
Colour temperature [K]:	4000
Material of the body:	PC
Colour of the body:	RAL7035; grey
Diffuser type:	OPAL; matt
Mounting version:	surface, suspended
Dimensions (H/W/T/S) [mm]:	1152/85/80; 1432/85/80;
Warranty [years]:	2 / 0.5 (battery); 5

CHARACTERISTICS

TYTAN 2 LED BASIC MULTI is a basic line of lighting fixtures that provides an excellent alternative to traditional fluorescent lamps. The lighting fixture has been designed from scratch. TYTAN 2 LED BASIC MULTI includes new solutions which improve the light distribution and the temperature balance. The new LED panels ensure high luminous efficacy up to 158 lm/W. This provides the required level of lighting along with significant energy savings. The lighting fixture includes many improvements which facilitate and speed up the installation process: a solution involving the integration of the diffuser with the LED panel, a diffuser suspension system, and adjustable mounting brackets with an installation tolerance of +/-50 mm. As a standard, the fixture is equipped with robust clips made of stainless steel (INOX). The body of the fixture and the diffuser are resistant to UV radiation. The MULTI luminaire version allows individual configuration: thanks to the built-in microswitch, it is possible to choose one of four settings (rated power of the luminaire [W]/luminous flux of the fitting [lm]): 18W-31W - 1. 18W/2700 lm; 2. 22W/3250 lm; 3. 26W/3800 lm; 4. 32W/4300 lm; 22W-38W - 1. 22W/3300 lm; 2. 27W/4000 lm; 3. 31W/4500 lm; 4. 38W/5300 lm; 26W-46W - 1. 26W/4050 lm; 2. 32W/4950 lm; 3. 39W/5800 lm; 4. 46W/6600 lm; 29W-51W - 1. 29W/4400 lm; 2. 37W/5400 lm; 3. 44W/6300 lm; 4. 51W/7150 lm; 32W-55W - 1. 32W/5050 lm; 2. 40W/6200 lm; 3. 47W/7250 lm; 4. 55W/8250 lm; 34W-59W - 1. 34W/5150 lm; 2. 42W/6200 lm; 3. 51W/7250 lm; 4. 59W/8150 lm;

APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level) , sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.

TYTAN 2 LED BASIC MULTI

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

TYTAN 2 LED BASIC MULTI 2700/3250/3800/4300lm

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Diffuser type	Through wiring	Motion sensor	Emergency lighting [h]	Dimensions (H/W/T/S) [mm]	Index
18/22/26/31	4000	2700/3250/3800/4300	matt			3	1152/85/80	>> 940873
18/22/26/31	4000	2700/3250/3800/4300	matt		yes	3	1152/85/80	>> 912108
18/22/26/31	4000	2700/3250/3800/4300	matt		yes		1152/85/80	>> 940859
18/22/26/31	4000	2700/3250/3800/4300	matt	LS2			1152/85/80	>> 940866
18/22/26/31	4000	2700/3250/3800/4300	matt				1152/85/80	>> 940842

TYTAN 2 LED BASIC MULTI 3300/4000/4500/5300lm

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Diffuser type	Through wiring	Motion sensor	Emergency lighting [h]	Dimensions (H/W/T/S) [mm]	Index
22/27/31/38	4000	3300/4000/4500/5300	matt			3	1432/85/80	>> 940996
22/27/31/38	4000	3300/4000/4500/5300	matt		yes		1432/85/80	>> 940972
22/27/31/38	4000	3300/4000/4500/5300	matt	LS2			1432/85/80	>> 940989
22/27/31/38	4000	3300/4000/4500/5300	matt				1432/85/80	>> 940965

TYTAN 2 LED BASIC MULTI 3700/4450/5250/6100lm

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Diffuser type	Through wiring	Motion sensor	Emergency lighting [h]	Dimensions (H/W/T/S) [mm]	Index
29/36/44/51	4000	3700/4450/5250/6100	OPAL	LS2 (2,5)			1152/85/80	>> 912306
29/36/44/51	4000	3700/4450/5250/6100	OPAL	LS2			1152/85/80	>> 912290
29/36/44/51	4000	3700/4450/5250/6100	OPAL		yes		1152/85/80	>> 912283
29/36/44/51	4000	3700/4450/5250/6100	OPAL				1152/85/80	>> 912276

TYTAN 2 LED BASIC MULTI 4050/4950/5800/6600lm

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Diffuser type	Through wiring	Motion sensor	Emergency lighting [h]	Dimensions (H/W/T/S) [mm]	Index
26/32/39/46	4000	4050/4950/5800/6600	matt		yes		1152/85/80	>> 912733
26/32/39/46	4000	4050/4950/5800/6600	matt	LS2 (2,5)			1152/85/80	>> 912757
26/32/39/46	4000	4050/4950/5800/6600	matt	LS2			1152/85/80	>> 912740
26/32/39/46	4000	4050/4950/5800/6600	matt				1152/85/80	>> 912726
26/32/39/46	4000	4050/4950/5800/6600	matt			3	1152/85/80	>> 912764

TYTAN 2 LED BASIC MULTI 4250/5250/6100/7000lm

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Diffuser type	Through wiring	Motion sensor	Emergency lighting [h]	Dimensions (H/W/T/S) [mm]	Index
32/40/47/55	4000	4250/5250/6100/7000	OPAL				1432/85/80	>> 912313
32/40/47/55	4000	4250/5250/6100/7000	OPAL		yes		1432/85/80	>> 912320
32/40/47/55	4000	4250/5250/6100/7000	OPAL	LS2			1432/85/80	>> 912337

TYTAN 2 LED BASIC MULTI

GENERAL CARD

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Diffuser type	Through wiring	Motion sensor	Emergency lighting [h]	Dimensions (H/W/T/S) [mm]	Index
32/40/47/55	4000	4250/5250/6100/7000	OPAL	LS2 (2,5)			1432/85/80	>> 912344

TYTAN 2 LED BASIC MULTI 4400/5400/6300/7150lm

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Diffuser type	Through wiring	Motion sensor	Emergency lighting [h]	Dimensions (H/W/T/S) [mm]	Index
29/37/44/51	4000	4400/5400/6300/7150	matt				1152/85/80	>> 940880
29/37/44/51	4000	4400/5400/6300/7150	matt		yes		1152/85/80	>> 940897
29/37/44/51	4000	4400/5400/6300/7150	matt	LS2			1152/85/80	>> 940903
29/37/44/51	4000	4400/5400/6300/7150	matt			3	1152/85/80	>> 940910

TYTAN 2 LED BASIC MULTI 5050/6200/7250/8250lm

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Diffuser type	Through wiring	Motion sensor	Emergency lighting [h]	Dimensions (H/W/T/S) [mm]	Index
32/40/47/55	4000	5050/6200/7250/8250	matt		yes		1432/85/80	>> 912573
32/40/47/55	4000	5050/6200/7250/8250	matt	LS2 (2,5)			1432/85/80	>> 912597
32/40/47/55	4000	5050/6200/7250/8250	matt	LS2			1432/85/80	>> 912580
32/40/47/55	4000	5050/6200/7250/8250	matt			3	1432/85/80	>> 912603
32/40/47/55	4000	5050/6200/7250/8250	matt				1432/85/80	>> 912566


TYTAN 2 LED BASIC MULTI 5150/6200/7250/8150lm

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Diffuser type	Through wiring	Motion sensor	Emergency lighting [h]	Dimensions (H/W/T/S) [mm]	Index
34/42/51/59	4000	5150/6200/7250/8150	matt		yes		1152/85/80	>> 940934
34/42/51/59	4000	5150/6200/7250/8150	matt	LS2			1152/85/80	>> 940941
34/42/51/59	4000	5150/6200/7250/8150	matt			3	1152/85/80	>> 940958
34/42/51/59	4000	5150/6200/7250/8150	matt				1152/85/80	>> 940927

TYTAN 2 LED BASIC MULTI

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE




TYTAN 2 LED

TYTAN 2 LED BASIC MULTI

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
16000507	Breathable gland gray M20*1.5 IP68
60000006	M16 stuffing box plug various PA black M-16 - BPM-21
907913	TYTAN LED. ATLAS LED - protective grid 1152mm
907920	TYTAN LED. ATLAS LED - protective grid 1432mm
80000378	Cable gland PG 13.5 Titanium PA 6.6 gray with nut



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



Breathable gland gray M20*1.5 IP68 (16000507)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)



TYTAN LED. ATLAS LED - protective grid 1152mm (907913)



TYTAN LED. ATLAS LED - protective grid 1432mm (907920)

Card creation date: 20 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 40/2022; 451/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl

