

# GIANT LED EVO

## GENERAL CARD



### TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	227.00; 288.00
Colour temperature [K]:	4000
Luminous flux [lm]*:	33144; 45000
Impact resistance:	IK10
Ingress protection:	IP44; IP54
Electrical protection class:	I
Energy efficiency class:	B; C
Colour of the body:	grey
Diffuser material:	PC
Diffuser type:	mat
Diffuser colour:	white
Dimensions (H/W/T/S) [mm]:	740/420/320;
Warranty [years]:	5

### CHARACTERISTICS

Lightweight and very powerful portable LED floodlight for professional use. Provides even and stable directional illumination. The lamp is made of impact-resistant polypropylene (PP). The anti-glare diffuser made of polycarbonate (PC), despite its matte surface, transmits up to 80% of the light emitted by the LED. It has an ergonomic carrying handle. Standard: rubber cable H07RN-F 3×1.5mm<sup>2</sup> (5m). With a variety of functions, the lamp is ideal for illuminating any workplace. The high luminous flux and the maximum degree of impact resistance are particularly important in the lighting of construction sites or in the work of services intervening at various emergencies. A high degree of waterproofness allows its use in the harshest weather conditions. Its light weight makes it easy to use for workplace lighting in industrial halls or finishing work.

### APPLICATION

Temporary lighting for construction site, finishing works, outdoor earthworks, road and highway repair, Especially useful for mobile services , emergency services, police, military, firefighters, construction crews, electricians, railroad repair, etc.

# GIANT LED EVO

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details


Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Ingress protection	Socket type	Plug type	Index
227	33144	4000	IP54	SCHUKO	UNI-SCHUKO	<a href="#">&gt;&gt; 901256</a>
227	33144	4000	IP44	DK	DK	<a href="#">&gt;&gt; 901270</a>
227	33144	4000	IP54	PL-FR	UNI-SCHUKO	<a href="#">&gt;&gt; 901263</a>
288	45000	4000	IP54	DK	DK	<a href="#">&gt;&gt; 901317</a>
288	45000	4000	IP54	PL-FR	UNI-SCHUKO	<a href="#">&gt;&gt; 901300</a>
288	45000	4000	IP54	SCHUKO	UNI-SCHUKO	<a href="#">&gt;&gt; 901294</a>

# GIANT LED EVO

## GENERAL CARD

## ACCESSORIES AVAILABLE

index	Name
000300	Adapter plate with click function for mounting the Giant Luminaire on the tripod
<a href="#">000294</a>	Steel tripod 3 m




Steel tripod 3 m (000294)

Card creation date: 21 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 08/2021; 125/2023; 128/2023