TYPE 101 LED

GENERAL CARD





TECHNICAL PARAMETERS

Ingress protection: IP54

Impact resistance: IK10

Rated power of the luminaire [W]*: 13.00 - 26.00

Luminous flux [lm]*: 1694 - 3387

Colour temperature [K]: 4000

Color rendering index (Ra) >: 80

SDCM: 3

Energy efficiency class: D

Electrical protection class: |; ||; |||

Diffuser material: PC

Diffuser type: transparent

Warranty [years]: 5

CHARACTERISTICS

- Power: 13W, 14W, 26W or 40W

- Light source: LED

- High ingress protection class IP54
- Made of painted frozen polycarbonate
- Designed for series connecting

APPLICATION

Thanks to its various functions, the lamp is ideal for illuminating car lifts, ducts, machines, workplaces, etc. High luminous flux and maximum degree of impact resistance are especially important for lighting the workplace. High degree of tightness allows for its use in the most difficult weather conditions. Numerous accessories provide a wide range of mounting possibilities so as to precisely direct the light beam leaving the worker's hands free.



TYPE 101 LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Supply voltage [V]	Through wiring	Electrical protection class	Index
13	4000	220 - 240		I	>> 888809
14	4000	DC 24		III	<u>>> 888786</u>
26	4000	220 - 240	LS2	II	<u>>> 316074</u>
26	4000	220 - 240		1	<u>>> 888854</u>



GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
899140	Mounting holder for the TYPE 101 lamp



Mounting holder for the TYPE 101 lamp (899140)

Card creation date: 09 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



