
GENERAL CARD





TECHNICAL PARAMETERS

Ingress protection: IP33

Rated power of the luminaire [W]*: 6.00

Luminous flux [lm]*: 590; 630

Colour temperature [K]: 3000; 4000

Color rendering index (Ra) >: 80

Energy efficiency class:

Material of the body: ABS

Colour of the body: white

Diffuser material: PC

Diffuser type: matt

Mounting version: surface

Dimensions (H/W/T/S) [mm]: 108/108/85;

Warranty [years]: 5

CHARACTERISTICS

SQ 100 LED PLUS N is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.



SQ 100 LED PLUS N

GENERAL CARD

AVAILABLE VERSIONS



Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	Index
6	3000	590	E	<u>>> 572654</u>
6	4000	630	E	<u>>> 572630</u>

Card creation date: 24 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).