

# SQ 100 LED PLUS P

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP44/20
<b>Rated power of the luminaire [W]*:</b>	6.00
<b>Luminous flux [lm]*:</b>	590; 630
<b>Colour temperature [K]:</b>	3000; 4000
<b>Color rendering index (Ra) &gt;:</b>	80
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	ABS
<b>Colour of the body:</b>	white
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	matt
<b>Mounting version:</b>	recessed
<b>Dimensions (H/W/T/S) [mm]:</b>	102/102/75;
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

SQ 100 LED PLUS P is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

## APPLICATION

Recessed-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.

# SQ 100 LED PLUS P

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	Index
6	3000	590	E	<a href="#">&gt;&gt; 572579</a>
6	4000	630	E	<a href="#">&gt;&gt; 572555</a>

Card creation date: 04 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 313/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl