

RQ 100 LED PLUS P

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|------------------------------------|------------|
| Ingress protection: | IP44/20 |
| Rated power of the luminaire [W]*: | 6.00 |
| Luminous flux [lm]*: | 590; 630 |
| Colour temperature [K]: | 3000; 4000 |
| Colour rendering index: | >80 |
| Energy efficiency class: | E |
| Material of the body: | ABS |
| Colour of the body: | white |
| Diffuser material: | PC |
| Diffuser type: | MAT |
| Mounting version: | recessed |
| Dimensions (H/W/T/S) [mm]: | 102/75; |
| Warranty [years]: | 5 |

CHARACTERISTICS

RQ 100 LED PLUS P is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Recessed-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.

RQ 100 LED PLUS P

GENERAL CARD

AVAILABLE VERSIONS

 Click index >>, to see details

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | DIMM DALI | Energy efficiency class | Index |
|-----------------------------------|------------------------|---------------------|-----------|-------------------------|---------------------------------|
| 6 | 3000 | 590 | | E | >> 572494 |
| 6 | 4000 | 630 | | E | >> 572470 |
| 6 | 4000 | 630 | yes | E | >> 572678 |