

RQ 100 LED PLUS P

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44/20
Rated power of the luminaire [W]*:	6.00
Luminous flux [lm]*:	590; 630
Colour temperature [K]:	3000; 4000
Color rendering index (Ra) >:	80
Energy efficiency class:	E
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	matt
Mounting version:	recessed
Dimensions (H/W/T/S) [mm]:	102/75;
Warranty [years]:	5

CHARACTERISTICS

RQ 100 LED PLUS P is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Recessed-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.

RQ 100 LED PLUS P

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	DIMM DALI	Energy efficiency class	Index
6	3000	590		E	>> 572494
6	4000	630		E	>> 572470
6	4000	630	yes	E	>> 572678

Card creation date: 03 June 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 316/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl